

alta vista™

floor/wall/countertop
ColorBody™ PORCELAIN



Desert Sand AV50



Sunset Gold AV51



Misty Rain AV52



Drift Wood AV53



sizes



18" x 18" Field Tile
(Nominal 17-7/8" x 17-7/8" x 1/4")
(Nominal 45.0 cm x 45.0 cm)
Sq. ft. per carton: 15.26 Pieces per carton: 7



12" x 12" Field Tile
(Nominal 11-3/4" x 11-3/4" x 1/4")
(Nominal 29.8 cm x 29.8 cm)
Sq. ft. per carton: 12.59 Pieces per carton: 13

Grout joint recommendation: 3/16"

shade variation:



Medium – Color variation within each tile.

trim detail:

Type	Number	Size
Bullnose	S-44C9	4" x 12"
Cove Base	S-36C9T	6" x 12"
Cove Base Corner	SC-36C9T	1" x 6"

approved usage: Floors, Walls, Countertops & Exteriors

F	W	C	E
Floors	Walls	Countertops	Exteriors

Water, oil, grease, etc. create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection. For additional product information, refer to "Factors to Consider" at www.daltile.com/ResidentialFactors.
Not for use on ramps.

durability:

Floor Wear Resistance

1	Residential Bathrooms
2	All Residential Areas
3	All Residential/Light Commercial
4	All Residential/Commercial

slip resistance (wet):

The higher the rating, the higher the slip resistance.

1	<.50
2	.50 - .59
3	≥.60

coordinating decorative accent ideas

Desert Sand	Sunset Gold
Tumbled Stone Coral TS27 Checkerboard Accent Strip 	Tumbled Stone Sand/Walnut TS24 Wide Accent Strip
Misty Rain	Drift Wood
Tumbled Stone Silver Gray/Copper/ Ocean Green TS80 Diamond Accent Strip 	Tumbled Stone Sand/Walnut TS12 Diamond Accent Strip

Note: Since there are variations in all fired ceramic products, the tile and trim supplied for your particular installation may not match these samples. Final selection should be made from actual tiles and trim, and not from tile and trim samples or color reproductions. Manufactured in accordance with ANSI A137.1 standards.

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the tile surface. Use of a latex modified thin-set is recommended for installation.



daltile®

7834 C.F. Hawn Freeway
Dallas, TX 75217
214-398-1411. 800-933-TILE

For more information about Daltile products and services, visit our website at daltileproducts.com