



White Orchid P320



Rice Paper P321



Sprout P322



Water Chestnut P323



Chai Tea P324



Morning Dove P325








Imperial Gray P326






Panda Black P327

Sizes

	Nominal	Sq. Ft. per carton	Pieces per carton
 24" x 24" Field Tile	(Nominal 24" x 24") (Nominal 60.0 cm x 60.0 cm)	15.49	4
 12" x 24" Field Tile	(Nominal 12" x 24") (Nominal 30.0 cm x 60.0 cm)	15.49	8
 12" x 12" Field Tile	(Nominal 12" x 12") (Nominal 30.0 cm x 30.0 cm)	10.65	11
 2" x 24" Field Tile	(Nominal 2" x 24") (Nominal 5.0 cm x 60.0 cm)	10.00	30
 2" x 2" Mosaic Sheet*	(Nominal 12" x 12") (Nominal 30.0 cm x 30.0 cm)	10.65	11

* Mosaic is Mesh Mounted on a 12" x 12" sheet.

Trim

Type	Number	Size	Pieces per carton
 Bullnose	S-43C9	3" x 12"	33
 Cove Base	S-36C9T	6" x 12"	30
 Cove Base Corner	SC-36C9T	1" x 6"	10

Note

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the surface. Use of a latex modified thin-set is recommended for installation.

Special care needs to be given when installing tiles 20" and larger. Please refer to www.daltileproducts.com/LargeTiles for additional information.


Since there are variations in all fired ceramic products, tile and trim supplied for your particular installation may not match these samples. Final color selection should be made from actual tiles and trim and not from tile and trim samples or color reproductions. Manufactured in accordance with ANSI A137.1 standards.

Application

	Residential	Light Commercial	Commercial	Exterior
Floors	❖	❖	❖	
Walls/Backsplashes	❖	❖	❖	❖
Counters	❖	❖	❖	❖
Pool Linings	❖	❖	❖	❖

Suitable for exterior walls in freezing and non-freezing climates when proper installation methods are followed.

Installation

Thickness	Grout Joint Recommendation	Shade Variation
3/8"	1/16" (1/8" when used in a pattern)	 (Medium)

Test Results



	ASTM#	Result
Water Absorption	C373	<0.5%
Breaking Strength	C648	>450 lbs
Scratch Hardness	MOH's	8.0
Chemical Resistance	C650	Resistant
Coefficient of Friction	C1028	Wet: ≥0.60 Dry: ≥0.70

TruEdge



Each tile is rectified and modular which allows for the use of smaller grout joints.

For additional information refer to "Factors to Consider" at: www.daltile.com/CommercialFactors

Water, oil, grease, etc. create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection. Not for use on ramps.