




coordinating decorative accent ideas

Techno Beige

Salerno Universal SL87



Techno Bronze

Massalia Bullion MS91 Pinnacle Accent



Techno Brown

Fashion Accents Illusion Taupe FA29 Accent




Techno Green

Cristallo Glass Peridot CR52 Chair Rail



Techno Gray

Urban Metals Stainless Arc UM01 Wall Liner




Techno Black

Metal Ages Polished Pewter MA11 Corbel Accent




field tile



Techno Beige VI50



Techno Bronze VI53




Techno Brown VI54



Techno Green VI52



Techno Gray VI51



Techno Black VI55

decorative accents



Techno Beige VI50 Decorative Accent



Techno Bronze VI53 Decorative Accent



Techno Brown VI54 Decorative Accent



Techno Green VI52 Decorative Accent



Techno Gray VI51 Decorative Accent



Techno Black VI55 Decorative Accent



sizes:

All sizes available in an unpolished and a light polished finish.

24" x 24" Field Tile Nominal: $23^{-1}/2^{11} \times 23^{-1}/2^{11}$ (59.8 cm x 59.8 cm) 3/8" thick Sq. ft. per carton: 15.49 Pieces per carton: 4

12" x 24" Field Tile Nominal: 11.3/4" x 23-1/2" (29.8 cm x 59.8 cm)

Sq. ft. per carton: 11.62 Pieces per carton: 6

18" x 18" Field Tile Nominal: 17.5/8" x 17.5/8" (44.8 cm x 44.8 cm) 3/8" thick

Sq. ft. per carton: 13.07 Pieces per carton: 6



12" x 12" Field Tile Nominal: 11.3/4" x 11.3/4" (29.8 cm x 29.8 cm) 3/8" thick

Sq. ft. per carton: 11.62 Pieces per carton: 12

2" x 12" Decorative Accent Nominal: 1-7/8" x 11-3/4" (4.8 cm x 29.8 cm) 3/8" thick Sq. ft. per carton: n/a Pieces per carton: 15

Grout joint recommendation: 1/16" or 1/8" when used in a pattern.

approved usage: Floors, Walls, Countertops & Exteriors



Water, oil, grease, etc. create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection. For additional product information, refer to "Factors to Consider" at www.daltile.com/ResidentialFactors. Not for use on ramps.

shade variation:



Medium (V2) – Color variation within each tile.

slip resistance (wet):

The higher the rating, the higher the slip resistance.


3 ≥.60

.50 - .59

trim detail:		
Туре	Number	Size
Bullnose	S-43C9	3" x 12"
Cove Base	S-36C9T	6" x 12"
Cove Base Outcor	ner SC-36C9T	1" x 6"
	•	

tile pattern guide

Alternating Vertical Pattern	Broken Joint Pattern	
Hansantah Battarn	Diamond Pattern	





Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the tile surface. Use of a modified latex thin-set is recommended for installation.

Special consideration needs to be given when installing tiles 20" and larger. Please refer to www.daltileproducts.com/LargeTiles for additional information.

Note: Since there are variations in all fired ceramic products, the tile and trim supplied for your particular installation may not match these samples. Final selection should be made from actual tiles and trim, and not from tile and trim samples or color reproductions. Manufactured in accordance





7834 C.F. Hawn Freeway Dallas, TX 75217 214-398-1411. 800-933-TILE

For more information about Daltile products and services, visit our website at daltileproducts.com

© 2008 Dal-Tile Corporation (3/08) SSDTVIBE