

GLAZED PORCELAIN

# DELMONOCO™



**daltile**<sup>®</sup>  
DESIGN WITH CONFIDENCE™

DEL MONOCO™

GLAZED PORCELAIN



*floor • wall • countertop*

Bask in the unparalleled potential of Daltile's Del Monoco™. Make any design come to life with the immense modular design possibilities of this dramatic floor and wall collection. Featuring a beautiful stone visual with unique shade variation in four warm colors, Del Monoco™ glazed porcelain tile is sophisticated and beautiful. The rounded edges express an elegant, remarkable quality that ushers the beauty of natural stone into any home or commercial environment.



Photo features Carmina Beige 20 x 20 in a diamond pattern.

*floor • wall • countertop*

DEL MONOCO™

GLAZED PORCELAIN

*Field Tile*



CARMINA BEIGE DM90



ADRIANA ROSSO



TATIANA NOCE DM92



LEONA GRIGIO DM93

*Wall Decorative Accents*



CARMINA BEIGE DM90  
3-1/4 x 6-1/2 Decorative Accent



ADRIANA ROSSO DM91  
3-1/4 x 6-1/2 Decorative accent



TATIANA NOCE DM92  
3-1/4 x 6-1/2 Decorative Accent



LEONA GRIGIO DM93  
3-1/4 x 6-1/2 Decorative Accent



CARMINA BEIGE DM90  
6-1/2 x 6-1/2 Decorative Accent



ADRIANA ROSSO DM91  
6-1/2 x 6-1/2 Decorative Accent



TATIANA NOCE DM92  
6-1/2 x 6-1/2 Decorative Accent



LEONA GRIGIO DM93  
6-1/2 x 6-1/2 Decorative Accent

## *Floor/Wall Decorative Border*



CARMINA BEIGE DM90  
3 x 13 Decorative Border



ADRIANA ROSSO DM91  
3 x 13 Decorative Border



TATIANA NOCE DM92  
3 x 13 Decorative Border



LEONA GRIGIO DM93  
3 x 13 Decorative Border

## *Backsplash Design Ideas*



Backsplash consists of 6-1/2 x 6-1/2 field tile in Adriana Rosso and Carmina Beige with 6-1/2 x 6-1/2 decorative accents in Carmina Beige.

## *Pattern Ideas*



ALTERNATING  
VERTICAL



HOPSCOTCH



CHECKERBOARD

## SIZES

		SQ.FT. CARTON	PIECES PER CARTON
20 x 20 Field Tile	19-3/4" x 19-3/4" (50.0 cm x 50.0 cm)	16.56	6
13 x 20 Field Tile	13-1/8" x 19-3/4" (33.3 cm x 50.0 cm)	12.90	7
13 x 13 Field Tile	13-1/8" x 13-1/8" (33.3 cm x 33.3 cm)	14.77	12
6-1/2 x 6-1/2 Field Tile	6-7/16" x 6-7/16" (16.5 cm x 16.5 cm)	12.19	40
3-1/4 x 6-1/2 Field Tile	3-1/4" x 6-7/16" (8.2 cm x 16.5 cm)	7.62	50
3 x 13 Decorative Border	3-1/4" x 13-1/8" (8.2 cm x 33.3 cm)	--	10
6-1/2 x 6-1/2 Wall Decorative Accent	6-7/16" x 6-7/16" (16.5 cm x 16.5 cm)	--	6
3-1/4 x 6-1/2 Wall Decorative Accent	3-1/4" x 6-7/16" (8.2 cm x 16.5 cm)	--	12
3 x 3 Mosaic (Mesh-mounted on 13 x 13 sheet)	Sheet 13-1/8" x 13-1/8" (Sheet 33.3 cm x 33.3 cm)	11.08	9

## RESIDENTIAL USAGE

FLOOR	WALL	COUNTERTOPS	EXTERIOR PATIOS	EXTERIOR POOL DECKS
F	W	C	EP	<del>ED</del>

Suitable for exterior floors (excluding pool decks) and walls in freezing and non-freezing climates when proper installation methods are followed.

## COMMERCIAL USAGE

	INTERIOR			EXTERIOR	
	LIGHT RESIDENTIAL	COMMERCIAL	COMMERCIAL	RESIDENTIAL	COMMERCIAL
Floors/Patios	✓	✓	✓	✓	
Walls/Backsplashes	✓	✓	✓	✓	✓
Countertops	✓	✓	✓	✓	✓
Pool Decking					
Pool Linings	✓	✓	✓	✓	✓

Suitable for exterior walls in freezing and non-freezing climates when proper installation methods are followed.



## TRIM

TYPE	NUMBER	SIZE	PIECES PER CARTON
Bullnose	S-43E9	3 x 13	28
Cove Base	S-36E9T	6 x 13	30
Cove Base Corner	SC-36E9T	1 x 6	15

## SHADE VARIATION



**RANDOM (V4)**  
Extreme color and texture variation from tile to tile and within each tile; a random look.

## INSTALLATION

THICKNESS	GROUT JOINT RECOMMENDATION
5/16"	3/16" Floor

## SLIP RESISTANCE (WET) : 3

The higher the rating, the higher the slip resistance.

1 < .50

2 .50 - .59

3 ≥ .60

## TEST RESULTS

	ASTM#	RESULT
Water Absorption	C373	<0.5%
Breaking Strength	C648	>400 lbs
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant
Coefficient of Friction	C1028	Wet: ≥0.60 Dry: ≥0.70
Abrasion Resistance	C1027	4

## NOTES

Use of a latex modified thin-set is recommended for installation.

Special care needs to be given when installing tiles 20" and larger. Please refer to [www.daltile.com/LargeTiles](http://www.daltile.com/LargeTiles) for information.

Strong random shading enhances the natural beauty of this product. To achieve optimal results, tile should be selected from multiple cartons and shading arrangement planned prior to installation.

Since there are variations in all fired ceramic products, the tile and trim supplied for your particular installation may not match these samples. Final color selection should be made from actual tiles and trim and not from tile and trim samples or color reproductions. Manufactured in accordance with ANSI A137.1 standards.

For additional information refer to "Factors to Consider" at: [www.daltile.com/CommercialFactors](http://www.daltile.com/CommercialFactors)

Water, oil, grease etc. create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection.  
Not for use on ramps.

# DEL MONOCO™

# GLAZED PORCELAIN



*floor • wall • countertop*



**daltile**  
**greenworks**  
ENVIRONMENTAL LEADERSHIP THAT WORKS

By their very design, Daltile products can help make it easier for you to earn LEED™ points and/or points towards many industry leading green home building programs. From using recycled material content to establishing manufacturing facilities within 500 miles of your project, we help ensure you don't have to compromise your design to be environmentally conscious. For detailed information, visit [daltilegreenworks.com](http://daltilegreenworks.com).



EXTERIOR  
PRODUCT



Printed using soy inks.

7834 C. F. Hawn Freeway | Dallas, TX 75217 | 214.398.1411 800.933.TILE  
For more information about Daltile products and services, visit our website at [daltile.com](http://daltile.com)

©2011 Daltile Corporation (111) SDDTMONOCO