pietre vecchie[™]

coordinating decorative medallions

Scroll Water Jet Medallion WJM3



Floral Water Jet Medallion WJM1



Florentine Medallion WJM4



field tile

Antique White PV01

Warm Walnut PV03



Champagne PV02



Golden Sienna PV04



tumbled mosaic

Antique White PV01

Champagne PV02

Warm Walnut PV03



Golden Sienna PV04



pietre vecchie[™]

sizes: 24" x 24" Field Tile Nominal: 24" x 24" (61.0 cm x 61.0 cm) $^3/8$ " thick Sq. ft. per carton: 16.03 Pieces per carton: 4 20" x 20" Field Tile Nominal: $19 \cdot 1/2$ " x $19 \cdot 1/2$ " (49.5 cm x 49.5 cm) 3/8" thick Sq. ft. per carton: 18.83 Pieces per carton: 7 13" x 13" Field Tile Nominal: $12^{7}/8$ " x $12^{7}/8$ " (32.7 cm x 32.7 cm) $\frac{3}{8}$ " thick

2" x 2" Tumbled Mosaic Nominal: $12^{-7}/8$ " x $12^{-7}/8$ " (32.7 cm x 32.7 cm) 5/16" thick

Sq. ft. per carton: 16.70 Pieces per carton: 14

Pieces per carton: 12 sheets 36 pieces per Sheet Mesh-mounted

Grout joint recommendation: 3/16"

shade variation:



daltile

Random – Extreme color and texture variation from tile to tile and within each tile; a random look.

trim detail:		
Туре	Number	Size
Bullnose	S-43E9	3" x 13"

approved usage: Floors, Walls, Countertops & Exteriors



Water, oil, grease, etc. create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection. For additional product information, refer to "Factors to Consider" at www.daltile.com/ResidentialFactors. Not for use on ramps.

Photo features Pietre Vecchie in Champagne 20" x 20" with Florentine Medallion.

durability:

Floor Wear Resistance

Residential Bathrooms All Residential Areas

All Residential/Light Commer All Residential/Commercial

The higher the rating, the higher the slip resistance.

.50 - .59 3 ≥.60

slip resistance (wet):

tile pattern guide		
Brick Pattern	Grid Pattern	
Hopscotch Pattern	Diamond Pattern	

Note: Since there are variations in all fired ceramic products, the tile and trim supplied for your particular installation may not match these samples. Final selection should be made from actual tiles and trim, and not from tile and trim samples or color reproductions. Manufactured in accordance with ANSI A137.1 standards.

Strong Random shading enhances the natural beauty of this product. To achieve optimal results, tile should be selected from multiple catrons and shading arrangement planned prior to installation. Use of a modified thin-set is recommended for installation.



7834 C.F. Hawn Freeway Dallas, TX 75217 214-398-1411. 800-933-TILE

For more information about Daltile products and services, visit our website at daltileproducts.com

© 2005 Dal-Tile Corporation (7/05) SSDTPTRVECA

