

GLAZED CERAMIC

SANDDALO™



SANDALO™ GLAZED CERAMIC



floor • wall • countertop

Take your space to a whole new level. The possibilities are endless with Daltile's distinctive Sandalo™ collection. Available in a multitude of sizes, with accents and trims to match, it is perfect for residential and light commercial applications. The soft colors emulate natural stone, but with the easy maintenance of tile. Complete your project with the beautiful floor, wall, and mosaic combinations of this dynamic and resourceful collection.



Photo features Sandalo 12 x 12 field tile in Castillian Gray in a grid pattern on the floor.

floor • wall • countertop

SANDALO™



GLAZED CERAMIC

Field Tile



SERENE WHITE SW90



ACACIA BEIGE SW91



CASTILLIAN GRAY SW92



RAFFIA NOCE SW93

Wall Tile



SERENE WHITE SW90



ACACIA BEIGE SW91



CASTILLIAN GRAY SW92



RAFFIA NOCE SW93

Decorative Accents



SMOKY TOPAZ BLEND SW97



ZIRCON BLEND SW98

Mosaic




UNIVERSAL MOSAIC 2 x 2 SW96

Backsplash Design Ideas




Pattern Ideas



BRICK PATTERN



GRID PATTERN
WITH ACCENT STRIP



DIAMOND PATTERN

SIZES

		SQ.FT. CARTON	PIECES PER CARTON
18 x 18 Floor Tile	17-3/4" x 17-3/4" (45.2 cm x 45.2 cm)	18.00	8
12 x 12 Floor Tile	11-13/16" x 11-13/16" (30.0 cm x 30.0 cm)	11.00	11
9 x 12 Wall Tile	8-15/16" x 11-15/16" (22.7 cm x 30.3 cm)	11.25	15
6 x 6 Wall Tile	6" x 6" (15.2 cm x 15.2 cm)	12.50	50
3 x 12 Floor/Wall Border	3" x 12" (7.9 cm x 30.0 cm)	--	48
2 x 2 Mosaic (Dot-mounted)	Sheet: 11-15/16" x 23-15/16" (Sheet 30.2 cm x 60.9 cm)	24.00	12

RESIDENTIAL USAGE

FLOOR	WALL	COUNTERTOPS	EXTERIOR PATIOS	EXTERIOR POOL DECKS
F	W	C		

Wall tile suitable for residential bathroom floors only, not subject to outside foot traffic.

Universal border suitable for residential and light commercial use only.

Suitable for exterior walls in non-freezing climates when proper installation methods are followed.

COMMERCIAL APPLICATION

	LIGHT COMMERCIAL	COMMERCIAL	COMMERCIAL EXTERIORS
Floors	◆	◆	
Walls/Backsplashes	◆	◆	
Countertops	◆	◆	
Pool Decking			
Pool Linings	◆	◆	

Suitable for exterior walls only in non-freezing climates when proper installation methods are followed.

SLIP RESISTANCE (WET) : 3

The higher the rating, the higher the slip resistance.

1 < .50

2 .50 - .59

3 ≥ .60 (Floor)

DURABILITY : 4

Floor Wear Resistance

1 Residential Bathrooms

2 All Residential Areas

3 All Residential | Light Commercial

4 All Residential | Commercial

NOTES

Since there are variations in all fired ceramic products, the tile and trim supplied for your particular installation may not match these samples. Final color selection should be made from actual tiles and trim and not from tile and trim samples or color reproductions. Manufactured in accordance with ANSI A137.1 standards.

For additional information refer to "Factors to Consider" at: www.daltile.com/CommercialFactors

Water, oil, grease etc. create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection. Not for use on ramps.

TRIM

TYPE	NUMBER	SIZE	PIECES PER CARTON
Floor Bullnose	P-43C9	3 x 12	30
Bullnose	S-4309	3 x 9	54
Bullnose Corner	SN-4309	3 x 3	32
Quarter Round	A-106	1 x 6	152
Quarter Round Corner	UC-106	1 x 1	40
Surface Bullnose	S-4269	2 x 6	100
Surface Bullnose Outcorner	SN-4269	2 x 2	50
Bullnose	S-4669	6 x 6	50
Bullnose Corner	SCRL-4669	6 x 6	50
Radius Bullnose	A-4200	2 x 6	100
Radius Bullnose Corner	AN-4200	2 x 2	200
Counter Rail	26CRWL	2 x 6	36
Counter Rail Corner	22CRCN	2 x 2	24
Mosaic Trim	S-886	2 x 2	108

SHADE VARIATION



HIGH (V3)

Some variation from tile to tile and within each tile

INSTALLATION

THICKNESS	GROUT JOINT RECOMMENDATION
5/16" Floor & Wall 1/4" Mosaic	3/16" Floor, 1/16" Wall 1/8" Mosaic

TEST RESULTS

	ASTM#	FLOOR/MOSAICS	WALL
Water Absorption	C373	< 3.0%	< 20.0%
Breaking Strength	C648	> 250 lbs	> 120 - 230 lbs
Scratch Hardness	MOHS	8.0	4.0 - 6.5
Chemical Resistance	C650	Resistant	Resistant
Coefficient of Friction	C1028	Wet: ≥ 0.60 Dry: ≥ 0.65	Wet: < 0.50 Dry: ≥ 0.80
Abrasion Resistance	C1027	4	--



daltile®