




coordinating decorative
accent ideas

Beach

Tumbled Stone
Sand TS21
Pebble Accent Strip



Sunrise

Tumbled Stone
Antalya Dark/Sienna Gold/
Mediterranean Ivory TS67
Diamond Accent Strip



Moss

Tumbled Stone
Silver Gray/Copper/Ocean Green TS80
Diamond Accent Strip



Redwood

Tumbled Stone
Emperador Dark/Crema Marfil/Rojo
Alicante TS58
Serpentine Mosaic Accent Strip




Rock

Terra Antica
Celeste/Grigio TA04
Decorative Border



Mountain

Tumbled Stone
Silver Gray TS27



Earth

Metal Ages Polished Pewter MA11
Corbel Accent



field tile



Beach CP80



Sunrise CP81



Moss CP82



Redwood CP83



Rock CP84




Mountain CP85




Earth CP86



sizes:

 18" x 18" Field Tile
Nominal: 17-11/16" x 17-11/16" (45 cm x 45 cm)
5/16" thick
Sq. ft. per carton: 17.43
Pieces per carton: 8

 12" x 12" Field Tile
Nominal: 11-13/16" x 11-13/16" (30 cm x 30 cm)
5/16" thick
Sq. ft. per carton: 15.49
Pieces per carton: 16

Grout joint recommendation: 3/16"

approved usage: Floors, Walls, Countertops & Exteriors

F W C E
Floors Walls Countertops Exteriors

Water, oil, grease, etc. create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection. For additional product information, refer to "Factors to Consider" at www.daltile.com/ResidentialFactors. Not for use on ramps.



shade variation:

 Medium (V2) – Color variation within each tile.





slip resistance (wet):
The higher the rating, the higher the slip resistance.

1	<.50
2	.50 - .59
3	≥.60

trim detail:

Type	Number	Size
 Bullnose	S-43C9	3" x 12"
 Cove Base	S-36C9T	6" x 12"
 Cove Base Corner	SC-36C9T	1" x 6"

tile pattern guide

<p>Brickwork Square Pattern</p> 	<p>Grid Pattern</p> 
<p>Hopscotch Pattern</p> 	<p>Diamond Pattern</p> 

Note: Since there are variations in all fired ceramic products, the tile and trim supplied for your particular installation may not match these samples. Final selection should be made from actual tiles and trim, and not from tile and trim samples or color reproductions. Manufactured in accordance with ANSI A137.1 standards.

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the tile surface. Use of a modified latex thin-set is recommended for installation.

