

florenza™

floor/wall/countertop

ColorBody™ PORCELAIN



dalTile®

## field tile

Sabbia FZ01



Oliva FZ02



Brun FZ03



Azzurro FZ04



## decorative accent

Sabbia/Brun FZ10 Accent



Oliva/Azzurro FZ11 Accent



## sizes



24" x 24" Field Tile  
(Nominal 23-1/2" x 23-1/2")  
(Nominal 59.8 cm x 59.8 cm)  
3/8" thick  
Sq. ft. per carton: 15.50  
Pieces per carton: 4



12" x 24" Field Tile  
(Nominal 11-3/4" x 23-1/2")  
(Nominal 29.8 cm x 59.8 cm)  
3/8" thick  
Sq. ft. per carton: 11.62  
Pieces per carton: 6



18" x 18" Field Tile  
(Nominal 17-5/8" x 17-5/8")  
(Nominal 44.8 cm x 44.8 cm)  
3/8" thick  
Sq. ft. per carton: 13.08  
Pieces per carton: 6



12" x 12" Field Tile  
(Nominal 11-3/4" x 11-3/4")  
(Nominal 29.8 cm x 29.8 cm)  
3/8" thick  
Sq. ft. per carton: 11.62  
Pieces per carton: 12



3" x 12" Decorative Accent  
(Nominal 2-3/4" x 11-3/4")  
(Nominal 6.9 cm x 29.8 cm)  
3/8" thick  
Pieces per carton: 10

Grout joint recommendation: 1/16"  
(1/8" when installing the tile in a pattern)

## approved usage: Floors, Walls, Countertops & Exteriors

<b>F</b>	<b>W</b>	<b>C</b>	<b>E</b>
Floors	Walls	Countertops	Exteriors

Water, oil, grease, etc. create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection. For additional product information, refer to "Factors to Consider" at [www.daltile.com/ResidentialFactors](http://www.daltile.com/ResidentialFactors). Not for use on ramps.

## shade variation:



Random – Extreme color and texture variation from tile to tile and within each tile; a random look.

## trim detail:

Type	Number	Size
Bullnose	S-44C9	4" x 12"
Cove Base	S-36C9T	6" x 12"
Cove Base Corner	SC-36C9T	1" x 6"

## durability:

Floor Wear Resistance

1	Residential Bathrooms
2	All Residential Areas
3	All Residential/Light Commercial
<b>4</b>	All Residential/Commercial

## slip resistance (wet):

The higher the rating, the higher the slip resistance.

1	<.50
2	.50 - .59
<b>3</b>	≥.60

## tile pattern guide

Modular Rectangle Pattern	Grid Pattern with Accent

**Note:** Since there are variations in all fired ceramic products, the tile and trim supplied for your particular installation may not match these samples. Final selection should be made from actual tiles and trim, and not from tile and trim samples or color reproductions. Manufactured in accordance with ANSI A137.1 standards.

Strong random shading enhances the natural beauty of this product. To achieve optimal results, tile should be selected from multiple cartons and shading arrangement planned prior to installation.

Special care should be taken when grouting with dark pigmented colors. A grout release is recommended to prevent finely powdered pigments from lodging in the pores of the tile surface.

**Installation Requirement:** For proper bonding, medium bed mortar should be utilized in installing tiles with a dimensional length size greater than 20" x 20", large rectangles or tiles with greater dimensional thickness than normal. Back buttering tiles of this nature in the installation process will also assure proper coverage for bonding.



daltile®

7834 C.F. Hawn Freeway  
Dallas, TX 75217  
214-398-1411. 800-933-TILE

For more information about Daltile products and services, visit our website at [daltileproducts.com](http://daltileproducts.com)



Each tile is rectified and modular which allows for the use of smaller grout joints.