



GLAZED CERAMIC | STRATFORD PLACE™



daltile®

GLAZED CERAMIC | STRATFORD PLACE™



floor • wall • countertop

Imagine being whisked away to a distant Roman courtyard. That's the feeling evoked by Stratford Place, with its travertine look and subtle, earthy hues. From floors to walls to mosaics in a variety of sizes and trim, Stratford Place embodies the elegance you're looking for.



Photo features Stratford Place in Dorian Grey 12 x 12 on the floor.
Wall and tub surround features Dorian Grey 10 x 14 wall tile and 2 x 9 universal decorative accent.

floor • wall • countertop

GLAZED CERAMIC

STRATFORD PLACE™

Field Tile



ALABASTER SANDS SD91



WILLOW BRANCH SD92



DORIAN GREY SD94



TRUFFLE FIELD SD93

Wall Tile



ALABASTER SANDS SD91



WILLOW BRANCH SD92



DORIAN GREY SD94



TRUFFLE FIELD SD93

Decorative Accents



UNIVERSAL DECORATIVE ACCENT SD90

Mosaic



STRATFORD BLEND SD95

CREATIVE IDEAS

Color



ALABASTER SANDS SD91



WILLOW BRANCH SD92



DORIAN GREY SD94



TRUFFLE FIELD SD93

Accent



SALERNO UNIVERSAL SL87
DECORATIVE ACCENT



TUMBLED STONE
WALNUT TS17
ROPE ACCENT STRIP




METAL SIGNATURES AGED
BRONZE MSI I
JARDIN FLOOR/WALL BORDER




CASTLE DEVERRE
UNIVERSAL CV14 ACCENT

Pattern Ideas



BRICK PATTERN



GRID PATTERN



GRID PATTERN
WITH ACCENT



DIAMOND PATTERN

GLAZED CERAMIC STRATFORD PLACE™

SIZES

		SQ. FT. CARTON	PIECES PER CARTON
18 x 18 Field Tile	17-3/4" x 17-3/4" (45.2 cm x 45.2 cm)	18.00	8
12 x 12 Field Tile	11-13/16" x 11-13/16" (30.0 cm x 30.0 cm)	11.00	11
10 x 14 Wall Field Tile	9-27/32" x 13-31/32" (25.0 cm x 35.5 cm)	14.58	15
6 x 6 Wall Field Tile	6" x 6" (15.2 cm x 15.2 cm)	12.50	50
2 x 9 Decorative Accent	2-3/8" x 9-7/8" (6.03 cm x 25.08 cm)		
2 x 2 Mosaic (2' x 1' Sheet Dot-mounted)	2" x 2" 4.9 cm x 4.9 cm (Sheet 60.96 cm x 30.48 cm)	24.00	12

RESIDENTIAL USAGE

FLOOR*	WALL**	COUNTERTOPS	EXTERIOR PATIOS	EXTERIOR POOL DECKS
F	W	C		

*Residential floors only not subject to outside foot traffic.

**Suitable for exterior walls in non-freezing climates when proper installation methods are followed.

COMMERCIAL APPLICATION

FLOOR

	LIGHT COMMERCIAL	COMMERCIAL	COMMERCIAL EXTERIORS
Floors	◆	◆	
Walls/Backsplashes	◆	◆	
Counters	◆	◆	
Pool Decking			
Pool Linings	◆	◆	

WALL/MOSAICS

	LIGHT COMMERCIAL	COMMERCIAL	COMMERCIAL EXTERIORS
Floors			
Walls/Backsplashes	◆	◆	◆
Counters	◆	◆	◆
Pool Decking			
Pool Linings			

Suitable for exterior walls only in non-freezing climates when proper installation methods are followed.








NOTES

Since there are variations in all fired ceramic products, the tile and trim supplied for your particular installation may not match these samples. Final color selection should be made from actual tiles and trim and not from tile and trim samples or color reproductions. Manufactured in accordance with ANSI A137.1 standards.

For additional information refer to "Factors to Consider" at: www.daltile.com/CommercialFactors

Water, oil, grease etc. create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection. Not for use on ramps.

TRIM

TYPE	SIZE	PIECES PER CARTON
 Bullnose P-43C9	3" x 12"	22
 Bullnose S-4310	3" x 10"	54
 Bullnose S-4669	6" x 6"	50
 Surface Bullnose S-4269	2" x 6"	100
 Radius Bullnose A-4200	2" x 6"	100
 Bullnose Corner SCRL-4669	6" x 6"	50
 Bullnose Corner SN-4310	3" x 3"	32
 Surface Bullnose Outcorner SN-4269	2" x 2"	25
 Radius Bullnose Corner AN-4200	2" x 2"	200
 Bullnose/Corner Mosaics S-886	2" x 2"	108
 Counter Rail 26CRWL	2" x 6"	36
 Quarter Round A-106	1" x 6"	152
 Counter Rail Corner 22CRCN	2" x 2"	24
 Quarter Round Corner UC-106	1" x 1"	40

SHADE VARIATION



HIGH (V3)

Color variation from tile to tile, and within each tile.

INSTALLATION

THICKNESS	GROUT JOINT RECOMMENDATION
5/16" (Wall & Floor), 1/4" (Mosaics)	3/16" (Floor), 1/8" (Mosaic) and 1/16" (Wall)

SLIP RESISTANCE (WET) : 3

The higher the rating, the higher the slip resistance.

1 < .50
2 .50 - .59
3 ≥ .60 (Floor)

DURABILITY : 4

Floor Wear Resistance

1 Residential Bathrooms
2 All Residential Areas
3 All Residential Light Commercial
4 All Residential Commercial

TEST RESULTS

	ASTM#	FLOOR	WALL	MOSAICS
Water Absorption	C373	< 3.0%	< 20.0%	< 3.0%
Breaking Strength	C648	> 250 lbs	100-230 lbs	> 250 lbs
Scratch Hardness	MOHS	8.0	4.0-6.5	8.0
Chemical Resistance	C650	Resistant	Resistant	Resistant
Coefficient of Friction	C1028	Wet: ≥ 0.60 Dry: ≥ 0.65	Wet: < 0.50 Dry: ≥ 0.80	Wet: ≥ 0.60 Dry: ≥ 0.65



RECYCLED
MATERIALS



daltile
greenworks™
ENVIRONMENTAL LEADERSHIP THAT WORKS



daltile®

7834 C. F. Hawn Freeway | Dallas, TX 75217 | 214.398.1411 | 800.933.TILE

For more information about Daltile products and services, visit our website at daltile.com.