

MG304

FEATURES



M-G304W right hand tub as shown

- ❖ Waterproof 15 ½” Walk-in Door
- ❖ Thermostatic Water Valve
- ❖ Inward Swinging Door
- ❖ Polished Finish
- ❖ Safety Grab Bar
- ❖ Tub filler
- ❖ Hand-held Shower
- ❖ Molded Seat – 17” High & 25” Wide
- ❖ Luxurious Head Rest Pillow
- ❖ Dual drain system
- ❖ Left and Right hand drains available
- ❖ Easy Installation (4-6 Hrs)
- ❖ Limited Life Time Warranty on the Door Seal

AVAILABLE IN FOUR VERSIONS:

- M-G304 – plain soaking tub
- M-G304A – 24 heated air jets
- M-G304W – 14 heated water jets
- M-G304WA – 14 heated water and 12 heated air jets system

TECHNICAL INFORMATION

- **Materials:** Acrylic Composite
- **Power Supply:** 110V, 2.25KW
- **Dimensions:** 52 x 29.5 x 40 IN (59in. with extension panel)
- **Water Usage:** 50-60 Gallons
- **Drain capacity:** 40 gallons per minute

PLUMBING REQUIREMENTS

- Unit is equipped with flexible, metal braided ½ inch water supply hose with ½ female threaded connectors
- Need to install hot and cold shutoffs with ½ male threaded nipples (not included)
- **Note:** The flexible drain hose that is included with this unit is for installation into a floor drain only. Substituting the existing drain show for a different one will not void the warranty as long as there is no damage or evidence of misuse.

ELECTRICAL INFORMATION

- **M-G304A** –Heated Air Jet Motor 110v 8A
(Dedicated line 12-2 wire with 110 volt, 15-20 amp GFCI breaker)
- **M-G304W** - Water pump 110-120V 6.5A and Inline heater 110V 14A
(Dedicated line 10-2 wire with 110 volt, 30 amp GFCI breaker)
- **M-G304WA** - Water pump 110-120V 6.5A, Air jet motor with heater 110 volt 8A, and Inline heater 110V 14A
(Dedicated line 10-2 wire with 110 volt, 30 amp GFCI breaker)

GENERAL INFORMATION

- **Note:** It is advised to have the tub onsite before preparing drain location. Please call with any questions regarding drain hookup.
- Unit **must** be leveled in its permanent position and all feet must be on the ground to fully support the tub. ***Please check fittings for tightness before final connections.*** Connections may have loosened during shipping. ***Manufacturer reserves the right to change specs or features at anytime. Please check to confirm details. 1-866-783-2661***

