

Thin Wall Heat Shrink Tubing



- Used for electrical insulation, wire harness, bundling, splices & terminations
- Flexible polyolefin tubing
- 2:1 Shrink ratio
- Rated for 600Volt 257°F (125°C) continuous operation
- Forms tough, smooth insulated covering resistant to common fluids and solvents
- Black color

| Cat No. | Length | Diameter Before Shrinking | Diameter After Shrinking | Bag Qty | Each Piece |
|---------|--------|---------------------------|--------------------------|---------|------------|
| 68030 | 6" | .078" | .029" | 50 | |
| 68032 | 6" | .098" | .039" | 50 | |
| 68034 | 6" | .137" | .059" | 50 | |
| 68036 | 6" | .211" | .098" | 10 | |
| 68038 | 6" | .250" | .117" | 10 | |
| 68040 | 6" | .367" | .176" | 10 | |
| 68042 | 6" | .484" | .234" | 10 | |
| 68044 | 6" | .827" | .390" | 10 | |
| Rolls | | | | | |
| 68050 | 660 Ft | .078" | .029" | 1 Roll | |
| 68052 | 660 Ft | .098" | .039" | 1 Roll | |
| 68054 | 660 Ft | .137" | .059" | 1 Roll | |
| 68056 | 330 Ft | .211" | .098" | 1 Roll | |
| 68058 | 330 Ft | .250" | .117" | 1 Roll | |
| 68060 | 165 Ft | .367" | .176" | 1 Roll | |
| 68062 | 165 Ft | .484" | .234" | 1 Roll | |
| 68064 | 165 Ft | .827" | .390" | 1 Roll | |

Heavy Wall Heat Shrink Tubing - Flame Retardant



- Wide shrinkage allows various shapes & contours to be accommodated with one size tubing
- Insulates & protects electrical splices & terminations where maximum flame retardancy & exceptional insulating & sealing characteristics are required

- High impact and abrasion resistance capable of withstanding severe mechanical abuse of U.R.D., submersible and direct burial installations
- Will not split or rupture during installation, even when overheated
- Thermoplastic melttable adhesive sealant liner provides complete environmental protection and insulation
- Flame retardant
- Meets: UL 486D, CSA C22.2 No. 198.2, ANSI C119.1, Western Underground Guides Nos. 2.4, 2.5, MIL-DTL-23053/15, IEEE 383 Vertical Flame Test, ANSI C37.20.2, ICEA S-19-8 and NEMA insulation thickness requirements
- Rated for 600-1000V, 194°F (90°C) continuous use
- Continuous operating temperature: -67°F to 230°F (-55°C to 110°C)
- Shrink temperature: 248°F (120°C)
- Black color

| Cat No. | Cable Range | Length | Diameter Before Shrinking | Diameter After Shrinking | Wall Thickness | Bag Qty | Each Piece |
|-------------|-------------|--------|---------------------------|--------------------------|----------------|---------|------------|
| 68004 | 12-6 AWG | 6" | .400" | .150" | .09" | 10 | |
| 68008 | 8-1/0 AWG | 6" | .750" | .220" | .09" | 10 | |
| 68011 | 2-4/0 AWG | 8" | 1.100" | .375" | .12" | 5 | |
| 68015 | 3/0-400MCM | 8" | 1.500" | .500" | .16" | 4 | |
| 68020 | 250-750MCM | 12" | 2.000" | .750" | .16" | 1 | |
| 48" Lengths | | | | | | | |
| 68022 | 12-6 AWG | 48" | .400" | .150" | .09" | 1 | |
| 68023 | 8-1/0 AWG | 48" | .750" | .220" | .09" | 1 | |
| 68024 | 2-4/0 AWG | 48" | 1.100" | .375" | .12" | 1 | |
| 68025 | 3/0-400MCM | 48" | 1.500" | .500" | .16" | 1 | |
| 68026 | 250-750MCM | 48" | 2.000" | .750" | .16" | 1 | |