



DESIGNER CONTOUR® ELECTROL® WITH BUILT-IN INFRARED REMOTE CONTROL

Automatic Electric Projection Screen Model


SPECIFICATION DATA

DA-LITE SCREEN COMPANY, INC.
3100 North Detroit Street
Post Office Box 137
Warsaw, Indiana 46581-0137
Phone: 574-267-8101
800-622-3737
Fax: 574-267-7804
Toll Free Fax: 877-325-4832
www.da-lite.com
e-mail: info@da-lite.com

SUGGESTED SPECIFICATIONS: _____ projection screen(s), _____ (H) x _____ (W), electrically operated 120 volt (60 Hz) not more than 1.2 amp. Shall have specially designed motor mounted inside the roller, to be three wire with ground, quick reversal type, oiled for life, with automatic thermal overload cutout, integral gears, capacitor and an electric brake to prevent coasting. To have preset but adjustable limit switches to automatically stop the picture surface in the "up" and "down" positions. The roller to be of rigid metal. Roller mounting brackets to be adjustable to allow centering or offsetting of the screen within the case. Screen case to be a two piece design made of extruded aluminum. Case to be finished in white lightly textured powder coat. Screen fabric to be flame retardant and mildew resistant fiberglass with black masking borders standard. Bottom of fabric shall be formed into a pocket holding a metal rod. Screen to include a three-position control switch, cover plate and 10' power cord with 3-prong plug. Screen to be listed by Underwriters' Laboratories.

Matte White, High Contrast Matte White and Video Spectra 1.5: Seamless in all sizes.

High Power®: Horizontal seam required when both dimensions exceed 6'.



VIDEO (NTSC 4:3) FORMAT DIMENSIONS (2" standard black drop at top)

Viewing Area		Nominal Diagonal		Overall Length of Case		Approx. Ship. Wt.	
H x W	Cm	In.	Cm	In.	Cm	Lbs.	Kg
43" x 57"	109 x 145	72"	183	74 1/4"	189	36	16.3
50" x 67"	127 x 170	84"	213	84 1/4"	214	39	17.7
57" x 77"	145 x 196	96"	244	98 1/4"	250	44	20.0
60" x 80"	152 x 203	100"	254	98 1/4"	250	44	20.0
69" x 92"	175 x 234	120"	305	110 1/4"	280	49	22.2

HDTV (16:9) FORMAT DIMENSIONS (2" standard black drop at top)

Viewing Area		Nominal Diagonal		Overall Length of Case		Approx. Ship. Wt.	
H x W	Cm	In.	Cm	In.	Cm	Lbs.	Kg
37 1/2" x 67"	95 x 170	77"	196	84 1/4"	214	39	17.7
45" x 80"	114 x 203	92"	234	98 1/4"	250	44	20.0
52" x 92"	132 x 234	106"	269	110 1/4"	280	49	22.2

SQUARE FORMAT DIMENSIONS (screens with ^ have 2" standard black drop at top)

Sizes		Overall Length of Case		Approx. Ship. Wt.	
H x W	Cm	In.	Cm	Lbs.	Kg
50" x 50"	127 x 127	64 1/4"	163	30	13.6
60" x 60"	152 x 152	74 1/4"	189	36	16.3
70" x 70"	178 x 178	84 1/4"	214	39	17.7
84" x 84"	213 x 213	98 1/4"	250	44	20.0
6' x 8' ^	183 x 244	110 1/4"	280	49	22.2
8' x 8'	244 x 244	110 1/4"	280	50	22.7

Overall case length dimensions $\pm 1/4$ ".

Detail dimensional drawings, wiring diagrams and installation instructions available upon request.

Specifications subject to change without notice.

Custom formats and sizes available upon request.

WHEN ORDERING, MARK APPROPRIATE SELECTIONS:

Select size from charts on the other side.

Select viewing surface:

- ☐ Matte White
- ☐ High Contrast Matte White
- ☐ High Power
- ☐ Video Spectra 1.5

Greenguard® and Greenguard® Children and Schools Certified.

Optional Accessories:

- ☐ No borders (Black masking borders standard).
- ☐ Key Locking Cover Plate.
- ☐ 220 Volt (50 Hz) Motor.
- ☐ Veneer Case Cover (Choose from seven standard veneers).

☐ Light Oak

☐ Medium Oak

☐ Natural Walnut

☐ Heritage Walnut

☐ Mahogany

☐ Cherry

☐ Honey Maple

☐ Graphite case color.☐ Black case (white standard).

Project:

Architect:

Phone:

Contractor:

Phone:

Supervisor:

Phone:

Supplier:

Date:

Revised:

DESIGNER CONTOUR® ELECTROL® WITH BUILT-IN INFRARED REMOTE CONTROL

METHODS OF INSTALLATION

CEILING/HOOK MOUNT BRACKET

