

Deftoil® Danish Oil Finish

Tung Oil-Urethane formula penetrates, seals, and protects in one easy application.

This unique blend of premium oil and polyurethane forms a protective barrier which penetrates into the wood not on it. Deftoil preserves the natural beauty of the wood and provides a hand rubbed finish.

Quick & Easy.

- Wipe-on, wipe-off.
- One step finishing saves time.
- No other finish required.
- Easy pour can.
- Easy touch-up.

Beautiful and Durable.

- Preserves and enhances the natural beauty of wood.
- Penetrates deep into the wood for greater protection.
- Will not chip, peel, or crack.
- Provides a hand-rubbed appearance without the effort.
- Resists water, alcohol and other common household chemicals.

Plenty of Uses.

- Furniture.
- Cabinets.
- Molding.
- Interior millwork.
- Doors.
- Picture frames.
- Crafts, toys, and much more.

Sizes & Colors.

- Available in seven popular colors:
- Sizes include: Pint, Quart, Gallon and 5-Gallon.



APPLICATION:

Wear rubber gloves while working with any stain or finish products.

1. Sand unfinished wood to proper smoothness.
2. Remove all sanding dust.
3. Shake Deftoil well before use.
4. Apply liberal amount over surface with cloth, brush, or roller.
5. Allow to penetrate for 30 minutes then wipe off excess.
6. Do not allow any excess oil to dry on the surface.

NOTE: Some open grain woods, can bleed excess oil. Should this happen, re-wipe the surface until the bleeding stops.

Exterior Deftoil Products



Exterior

- One step protection for exterior wood.
- Long lasting UV, mildew and moisture protection.
- Will not chip, peel, or crack.
- Excellent for doors, furniture, gates, and handrails.



Marine Teakwood

- One step protection for dense woods such as Teak, White Oak, Mahogany, and Eucalyptus.
- Will not chip, peel, or crack.
- Excellent UV and moisture resistance.
- Hardens in the wood not on the wood.



Tel: (800) 458-3338
Fax: (330) 821-8019
Email: AskDeft@deftfinishes.com
Web Site: www.deftfinishes.com/trade





The Wood Finish People

PRODUCT INFORMATION

DEFTOIL® DANISH OIL FINISH

DESCRIPTION: Deftoil is a penetrating Danish Oil Finish formulated with Tung Oil and Urethane resins which penetrates into the wood not on it. Deftoil preserves the natural beauty of wood and provides a hand rubbed finish. Resists water, alcohol, and other common household chemicals.

SPECIFICATIONS

SOLVENT TYPE

Mineral Spirits

RESIN TYPE

Tung Oil, Linseed Oil, and Modified Urethane

FINISH

Very low sheen when applied to bare wood.

COLORS

Clear Natural, Light Walnut, Medium Walnut, Dark Walnut, Black Walnut, Fruitwood, and Golden Oak.

BASES

Not available

VISCOSITY AT 77 °F (25 °C)

39 - 41 sec. EZ#1 (Zahn Cup)

VOC CONTENT

Available at 250 g/L and at 550 g/L (as supplied).

SOLIDS BY VOLUME*

250 VOC: 68 ± 1%

550 VOC: 36 ± 1%

SOLIDS BY WEIGHT*

250 VOC: 72 ± 1%

550 VOC: 40 ± 1%

WEIGHT PER GALLON

7.2 - 7.6

COMPOSITION BY WEIGHT

	250 VOC	550 VOC
Vehicle	72 %	40 %
Solvents and additives	28 %	60 %

RECOMMENDED FILM THICKNESS PER COAT

Since all DEFTOIL has to penetrate the wood, the film thickness has no significance, and cannot be measured.

PRACTICAL COVERAGE PER COAT AT THE RECOMMENDED DRY FILM THICKNESS

250 VOC: 400 sq. ft./gal. 550 VOC: 550 sq. ft./gal. (depending on surface conditions)

AVERAGE DRY TIME AT 77 °F (25 °C)

Wipe off all excess after 30 minutes

Recoat: 1 hour Final coat: Allow 24 hours dry

Allow at least 1 week to develop water resistance

APPLICATION EQUIPMENT

Cloth, Brush, or Roller.

PACKAGING

Quart, Gallon, and 5-Gallon Pail.

MATERIAL SAFETY DATA SHEET

www.deftfinishes.com/trade

SURFACE PREPARATION

All surfaces must be cured, clean, dry, and free from dirt, dust, rust, stains, grease, oil, mildew, wax, efflorescence, and other contaminants. Remove all loose, peeling, or cracked coatings. Repair all cracks, holes, and other surface imperfections with a suitable patching material. Repaired surfaces should then be sanded, and cleaned. Deftoil must penetrate the wood and cannot be applied to a sealed surface, completely remove any coating.

THINNING RECOMMENDATIONS

Deftoil is supplied at application viscosity. Thinning is not recommended.

CLEANUP

Use Mineral Spirits for cleanup. Dispose of waste in accordance with applicable laws and regulations.

OTHER SYSTEM INFORMATION

If additional protection is needed or a higher gloss appearance is desired, top coat with Clear Wood Finish Brushing Lacquer, Waterborne Acrylic Finish, Deftthane or Water Base Polyurethane.

SPONTANEOUS COMBUSTION

Rags, steel wool or other waste soaked with DEFTOIL may spontaneously catch fire if improperly discarded. **IMMEDIATELY AFTER USE**, place rags, steel wool or other waste in a sealed water filled container.

WARNING

COMBUSTIBLE, Deftoil contains Mineral Spirits, a combustible solvent. Provide adequate ventilation and avoid all ignition sources during application and drying.

*Not specification values. Representative values calculated based on product formulas and ingredient characteristics as reported to Deft by suppliers.