

### RAY F2 ECO

Mounting	: Floor
Lamps description	: 1 x 26W GX24q3 FL
Environment	: Indoor
Finish	: White, Black, Transparent
Notes	: New halogen lamp "Energy saver" (consumption of a 70W and light emission similar to a 100W)
Technical description	: Floor lamp providing diffused lighting. Steel tube structure, welded, brushed and chrome-plated. Diffuser support in die-cast, polished and chrome-plated Zamak alloy. Injection-molded PA6 (nylon) lamp-cover. Color: white. Injection-molded PC (polycarbonate) inner diffuser. Color: 3% opal. Injection-molded elastic PVC (polyvinylchloride) feet. Lathe-shaped aluminum diffusers, painted white on the inside, and shiny white or black on the outside or gray-colored, blown and overlaid glass with glossy external finish. Resistive dimmer wired on cord for 0-100% light adjustment. Power cord with black PVC/PVC (flat)

### ELECTRICAL

Control gear availability	: Included
Control gear mounting	: Integral
Control gear type	: Electronic
Emergency	: Without
Switching	: ON-OFF switch and 0/100% dimmer installed on the cord
Voltage (V)	: 120

### PHYSICAL

Diameter (inch)	: 16.9
Supply	: Power cord
Weight (lbs)	: 20,2



**Ray F2 ECO**  
design by Rodolfo Dordoni

Floor lamp with diffused light emission

### Reference Code

- **FU592630**      **Black**
- **FU592609**      **White**
- **FU592520**      **Glass**

### Certifications

