

Important: Always disconnect the power before installing or replacing bulb and before cleaning or other maintenance.

This light should be installed by a licensed electrician

LAMP INSTALLATION AND ASSEMBLY

1. Shut off power to the outlet box. (fig. A)
2. Attach the mounting plate to the outlet box using outlet box screws.
3. Install B11 medium base bulbs. (not included)
4. Attach metal ring to glass by aligning metal ring holes to glass holes, insert glass holder threaded rods, tighten with cap nuts and plastic flat washers.
5. Connect fixture stem to hang straight by turning bottom part of hang straight. do not turn fixture stem or socket body.
6. Determine the height at which the fixture is to be hung. Screw together stem sections to achieve desired length.
7. Make appropriate electrical connections using wire nuts:
 - a. Connect the fixture's live wire (black) to the live outlet box wire.
 - b. Connect the fixture's neutral wire (white) to the neutral outlet box wire.
 - c. Connect fixture's ground wire (green or uncoated) to the ground outlet box wire. If no ground is present in outlet box, connect fixture's ground wire to the mounting plate using the green screw (included).
 - d. Carefully place connections in outlet box.
8. Attach canopy to mounting plate with canopy nuts.
9. Restore power to the fixture.

CARE INSTRUCTIONS

Dusting – Use a clean, dry cloth.

Cleaning – To protect the finish, avoid any harsh abrasives or chemicals.

