

Important: Always disconnect the power before installing or replacing bulb and before cleaning or other maintenance.

This light should be installed by a licensed electrician

LAMP INSTALLATION AND ASSEMBLY

1. Shut off power to the outlet box. (fig. A)
2. Attach the mounting plate to the outlet box using outlet box screws. Use mounting screws and anchors for extra support.
3. Install A19 bulbs. (not included)
4. Attach upper plastic washers, glass diffuser, lower plastic washers and lower discs to fixture threaded stems 2, tighten with finials.
5. Attach shade and flat washer to fixture stems 1.
6. Determine the height at which the fixture is to be hung. Screw together stem sections to achieve desired length, and tighten fixture stems 1.
7. Make appropriate electrical connections using wire nuts:
 - a. Connect the fixture's live wire (black) to the live outlet box wire.
 - b. Connect the fixture's neutral wire (white) to the neutral outlet box wire.
 - c. Connect fixture's ground wire (green or uncoated) to the ground outlet box wire. If no ground is present in outlet box, connect fixture's ground wire to the mounting plate using the green screw (included).
 - d. Carefully place connections in outlet box.
8. Attach canopy to mounting plate with canopy nuts.
9. Restore power to the fixture.

CARE INSTRUCTIONS

Dusting – Use a clean, dry cloth.

Cleaning – To protect the finish, avoid any harsh abrasives or chemicals.

