## STEAM HOSE



#### **BULK HOSE - BLACK**

Apache P/N	I.D. x O.D.	W.P.	Wt.Ft.
11027200	1/2" x 1-1/16"	250#	.38#
11027201	3/4" x 1-9/32"	250#	.52#
11027202	1" x 1-17/32"	250#	.77#
11013588	1-1/4" x 1-7/8"	250#	1.24#
11013609	1-1/2" x 2-3/16"	250#	1.44#
11013692	2" x 2-11/16"	250#	1.88#

**Application:** For high pressure saturated and superheated steam service (up to 250 P.S.I. and  $406^{\circ}$ F) where cover may come in contact with oil or grease.

**Construction:** Carbon steel wire reinforcement. Black EPDM tube and cover.

Temp. Range: Up to 406°F.

**Couplings:** Assembled with permanent hydraulic crimp type or 2 and 4 bolt interlocking clamp and insert type couplings. "Boss" male stems and female ground joint fittings are recommended for steam service.

Std. Bulk Length: 50' Note: Add 5% for red cover.

STEAM HOSE WARNING: The potential danger from steam in industrial hose applications is due to the great heat and pressures involved. Water changes to steam at higher temperatures when under pressure. The greater the pressure the higher the temperature required. If the steam escapes, tremendous quantities of heat are released very suddenly as the steam changes state (wet saturated, dry saturated, and super heated) and finally changes back to water. This, combined with the high pressure, provides the potential danger to operators. (Refer to RMA Publication lp-11-1 Steam Hose; Manual for Maintenance, Testing and Inspection).

# **RUBBER PRESSURE WASHER HOSE**









### 3000# - 3/8" HOSE ASSEMBLIES

Apache P/N	Length	Coupled	Color	Wt.Ft.
98388073	25'	1/4" MPT x 1/4" Male Pipe Swivel	Black	5.4#
98388078	35'	1/4" MPT x 1/4" Male Pipe Swivel	Black	7.2#
98388075	25'	3/8" MPT x 3/8" Male Pipe Swivel	Black	5.4#
98388080	35'	3/8" MPT x 3/8" Male Pipe Swivel	Black	7.2#
98388085	50'	3/8" MPT x 3/8" Male Pipe Swivel	Black	11.9#
98382305	100'	3/8" MPT x 3/8" Male Pipe Swivel	Black	24.0#
98388076	25'	3/8" MPT x 3/8" Male Pipe Swivel	Blue	5.4#
98388081	35'	3/8" MPT x 3/8" Male Pipe Swivel	Blue	7.2#
98388086	50'	3/8" MPT x 3/8" Male Pipe Swivel	Blue	11.9#
98388087	75'	3/8" MPT x 3/8" Male Pipe Swivel	Blue	18.0#

**Applications:** Use as a replacement or extension hose on gas/electric pressure washers rated up to 3000 PSI. Use this hose for hot and cold water applications where heavy-duty, high-pressure cleaning equipment is required.

**Assemblies:** High-tensile steel, one wire braid hose with bend restrictor.

Features: Blue hose is non-marking.

**Temp Range:** Laboratory tested for normal service from -4°F to 210°F (-20°C to 99°C).

Other lengths and sizes available upon request.

WARNING: Not for steam service.

# 4000# - 3/8" HOSE ASSEMBLIES

Apache P/N	Length	Coupled	Color	Wt.Ft.
10085560	25'	3/8" MPT x 3/8" Male Pipe Swivel	Black	7.25#
10085563	25'	Metric - F x F, w/Male Metric Adapter	Black	7.25#
10085564	25'	Quick Disconnect - 3/8" Socket x 3/8" Plug	Black	7.25#
10085570	50'	3/8" MPT x 3/8" Male Pipe Swivel	Black	12.9#
10085573	50'	Metric - F x F, w/Male Metric Adapter	Black	12.9#
10085574	50'	Quick Disconnect - 3/8" Socket x 3/8" Plug	Black	12.9#

**Applications:** Use as a replacement or extension hose on gas/electric pressure washers rated up to 4000 PSI. Use this hose for hot and cold water applications where heavy-duty, high-pressure cleaning equipment is required.

**Assemblies:** High-tensile steel, two wire braid hose with two bend restrictors.

Male Metric Adapter: Use to connect two female metric ends together.

**Temp Range:** Laboratory tested for normal service from -4°F to 210°F (-20°C to 99°C).

Other lengths and sizes available upon request.

WARNING: Not for steam service.