

SPRAY NOZZLES



VARIABLE SPRAY NOZZLES

| Apache P/N | Inlet | W.P. | Temp. | Orifice | Wt.Ea |
|------------|-----------|-------|-------|---------|-------|
| 99023465-C | 1/4" FNPT | 3000# | 176°F | 4.0 | .40# |
| 99023466-C | 1/4" FNPT | 3000# | 176°F | 4.5 | .35# |

Applications: General-purpose nozzle for most pressure washer situations. The push pull movement changes the spray from low (soap dispensing) to high pressure, turning the nozzle adjusts the spray pattern from a 0° to 80° fan.

Installation: Nozzle can be threaded directly onto 1/4" MNPT wand or for a quick/easy connection, use the optional QD socket and plug set.

Note: Use Teflon™ pipe tape on MNPT threads to ensure a leak-free connection.

HARD/SOFT TURBO NOZZLE W/FILTER

| Apache P/N | Inlet | PSI | Wt.Ea |
|------------|----------------------------|-------|-------|
| 99030688-C | 1/4" Quick Disconnect Plug | 3700# | 1.00# |

Applications: Turbo increases cleaning efficiency up to 200%, and filter extends the service life of the nozzle. Quick disconnects create a quick and easy "tool free" connection for nozzles and accessories.

Features: Push/pull movement to change from a soft spray (for cleaning wood) to high pressure. Easy clean filter; unscrew the quick disconnect plug from the turbo nozzle, then unscrew the filter to remove it for cleaning.

Installation: Requires a 1/4" quick disconnect socket on wand. Simply pull back on the quick disconnect socket collar to insert or release the hard/soft turbo nozzle. Quick disconnect socket also accepts other tips and accessories.

TURBO NOZZLES

| Apache P/N | Description | W.P. | Max. Temp. | Orifice | Wt.Ea |
|------------|-------------------------|-------|------------|---------|-------|
| 99032013-C | 1/4" Female Pipe Thread | 4000# | 212°F | 3.5 | 1.0# |
| 99023505 | 1/4" Female Pipe Thread | 5000# | 212°F | 5 | 1.6# |
| 99023483 | 1/4" Female Pipe Thread | 5000# | 212°F | 5.5 | 1.6# |
| 99023489 | 1/4" Female Pipe Thread | 5000# | 212°F | 6 | 1.6# |
| 99023575 | 1/4" Female Pipe Thread | 5000# | 212°F | 4.5 | 1.6# |

Applications: Use turbo nozzle to increase the cleaning efficiency (up to 200%) of your pressure washer. This nozzle covers a larger area more quickly than other nozzles, saving cleaning time.

Installation: Nozzle can be threaded directly onto 1/4" male pipe thread wand, or for a quick and easy connection, use a quick disconnect plug.

Note: Using a turbo filter (#99030576-C) is recommended to prolong the service life of the nozzle. Use pipe tape on male pipe threads to ensure a leak-free connection. Other orifice sizes are available.

