

# Evolution Board

with Deluxe Aluminum Trim



Full-length map rail with Colored Cork insert.



Accessory tray includes Dura-Safe® rubber end caps to eliminate sharp corners.





### Evolution Board with Deluxe Aluminum Trim

- The versatile Evolution Board is the ideal choice for a multipurpose audio/visual environment. The specially engineered magnetic porcelain steel surface provides rich and vivid projector images and doubles as a markerboard.
- Low gloss matte gray finish provides exceptional sharpness and clarity, eliminating projection dullness caused by external light sources.
- Surface requires weekly cleaning with a damp cloth for optimum performance. A small amount of marker ghosting may occur.
- Anodized aluminum trim has a 3/8" profile with hairline mitered corners. Black aluminum trim available at an upcharge. Features a full-length tackable map rail and a full-length accessory tray with rubber Dura-Safe® end caps to eliminate sharp corners.
- Made in the USA. TAA compliant. 50 year guarantee.

#### A. Evolution Board - Deluxe Aluminum Trim

Part No.	Dimensions	Ship Wt.
404AA-52*	1 1/2'H x 2'W	10 lbs
404AB-52*	2'H x 3'W	20 lbs
■ 404AC-52**	3'H x 4'W	36 lbs
■ 404AD-52	4'H x 4'W	69 lbs
■ 404AF-52	4'H x 5'W	84 lbs
■ 404AG-52	4'H x 6'W	94 lbs
■ 404AH-52	4'H x 8'W	120 lbs
404AK-52	4'H x 10'W	146 lbs
404AM-52	4'H x 12'W	194 lbs
404AP-52	4'H x 16'W	243 lbs

Made in the USA.

\*Ships UPS \*\*Ships UPS OS1

Due to shipping restrictions, boards listed as 3'H x 4'W actually measure 33 3/4"H x 48"W.

### Technical Specifications

- Multipurpose magnetic surface that provides exceptional sharpness and clarity with projected images, and excellent writability for dry erase markers.
- Good color contrast with 60% less glare than standard porcelain steel surfaces.
- Damp erasing is required for optimum performance. Some ghosting may occur.
- A precisely balanced porcelain enamel ground coat is furnace-fused to both sides of 28 gauge (standard) or 24 gauge (custom) steel.
- The first furnace fuses a ground coat of enamel that is heat-softened at approximately 1450° F. The second furnace firing fuses a coat of enamel to the ground coat enamel. Color Fusion ceramic top coat is applied providing the desired surface color.
- A fade resistant waterproof resin glue bonds the porcelain to a moisture-resistant core. Custom sizes are available.



Balt® & Best-Rite® are brand divisions of MooreCo Inc.

2885 Lorraine Ave | Temple, TX 76501  
p: 800.749.2258 | f: 800.697.6258

[www.moorecoinc.com](http://www.moorecoinc.com)