

L E U C O S[®]

INSTRUCTIONS FOR INSTALLATION - LEUCOS USA

SPHERA T 20 - SPHERA T 29 - SPHERA TR 37

A1 Enclosed



One installer



Save instructions

Revised
17 Luglio 2006

WARNING:

- DISCONNECT POWER BEFORE INSTALLATION.
- FIXTURE TO BE INSTALLED BY A CERTIFIED ELECTRICIAN.
- INSTALL IN ACCORDANCE WITH THE NATIONAL AND LOCAL ELECTRICAL CODES.
- TAKE GREAT CARE TO AVOID SCRATCHING OR CHIPPING THE GLASS WHEN, CARRYING OUT THE OPERATIONS BELOW

ATTENTION IN CASE OF DAMAGE OF THE FLEXIBLE SUPPLY CABLE, SUBSTITUTION SHOULD BE CARRIED OUT BY THE CONSTRUCTOR, CLIENT SERVICE OR QUALIFIED

Handle the glass shade carefully in order not to scratch it.

1. Place fixture in an upright position.
2. Insert light Bulb.
3. Insert the hole of the glass diffuser through the bulb and screw it moderately taking care to not tighten it too much.
4. Plug fixture to outlet.

SPHERA T 20 max 1x60 W 120V E12 Type G-16½ candelabra 

SPHERA T 29 max 1x100 W 120V E26 Type A-19 

SPHERA TR 37 max 1x100 W 120V E26 Type A-19 

SPHERA TR 37 max 1x150 W 120V E26 Type A-21 

For additional information please contact your local dealer
or **LEUCOS U.S.A.** at: Tel. (732) 225-0010 Fax. (732) 225-0250

