


L E U C O S<sup>®</sup>

INSTALLATION INSTRUCTIONS - LEUCOS USA



## KUBE T 3

A1 Enclosed



One installer



Save instructions

Revised  
26 September 2005

### WARNING:

- DISCONNECT POWER BEFORE INSTALLATION.
- FIXTURE TO BE INSTALLED BY A CERTIFIED ELECTRICIAN. INSTALL IN ACCORDANCE WITH THE NATIONAL AND LOCAL ELECTRICAL CODES.
- TAKE GREAT CARE TO AVOID SCRATCHING OR CHIPPING THE GLASS WHEN , CARRYING OUT THE OPERATIONS BELOW

ATTENTION IN CASE OF DAMAGE OF THE FLEXIBLE SUPPLY CABLE, SUBSTITUTION SHOULD BE CARRIED OUT BY THE CONSTRUCTOR, CLIENT SERVICE OR QUALIFIED PERSONNEL, IN ORDER TO AVOID DANGER.

- .1. Place the bulb into the lampholder "D" and make a working test then disconnect the plug again.
- .2. Make sure the three threaded thumb screws "B" are completely unscrewed inside the lower housing as shown.
- .3. Guide the base inside the diffuser opening then tighten again the three thumb screws "B" till a complete locking of the structure.

DO NOT USE TOOLS.

### FOR USA MARKET ONLY :

KUBE T3 : max 1x100 W 120V E26 Type A 

For additional information please contact your local dealer  
or **LEUCOS U.S.A.** at: Tel. (732) 225-0010 Fax. (732) 225-0250

