

R - 1872 Over the Range Convection Microwave Oven





over the range convection 1.1 cu. ft. 850 watts



cookware 9" x 13" oblong 4.5 qt. oval / 5 qt. round



13" ceramic turntable



Ideal for 6-8 servings



eatures

- Beautiful Bisque styling with glass window, compliments other bisque or almond appliances.
- Compu Broil®, Compu Roast® & Compu Bake® settings provide a new level of automatic ease.
 Broil a steak, roast a chicken or bake a cake to perfection at the touch of a key.
- Large 13-inch diameter ceramic turntable– offers ON/OFF flexibility to handle oversized or oblong-shaped dishes or containers.
- Sensor Cook® includes 12 Smart & Easy® sensor settings for the most popular microwaved foods. No need to set times or power levels— and no quesswork!

- Interactive Cooking System with Custom Help[®] includes options for English, Spanish or French.
- CompuDefrost[™] quickly defrosts meats and poultry by weight. Specific program for each category assures excellent, even results.
- Keep Warm lets you keep hot food hot up to 30 minutes after cooking is finished with no loss of food quality.
- Built-in Exhaust System offers horizontal or vertical discharge or ductless recirculation. It comes with a hood light and powerful fan.
- · High Rack is included for two-level baking.
- Low Rack may be used for baking, roasting or broiling.



R-1872 Over the Range Convection

Specifications

O p c c i i i c a t i o ii s	
OVEN CAPACITY	1.1 cu. ft.
COOKING UNIFORMITY	Turntable System with On/Off setting 13" diameter ceramic turntable
DISPLAY	7-digit, 2-color, lighted
CONTROL	Auto-Touch Controls
SPECIAL FEATURES	Keep Warm, Automatic Popcorn Sensor, Sensor Cook, Reheat Sensor, Convection Temperature Control (100°F-450°F), Low Mix/Bake, High Mix/Roast, Broil, Slow Cook, CompuBroil, CompuRoast, CompuBake, CompuDefrost Center, (ground meat, steaks, chicken pieces), Custom Help, Minute Plus, Kitchen Timer, 4-Stage Programming, 11 Variable Power Levels, 2-Speed Ventilation Fan, Light, Child Lock, Audible Signal Elimination, Demonstration Mode
COLOR	Bisque with glass window
OVEN INTERIOR	Stainless steel with light
OUTPUT POWER	850 Watts
OUTSIDE DIMENSIONS (WHD) 29 ¹⁵ /16" x 16 ¹¹ /32" x 15 ⁹ /32"
OVEN DIMENSIONS (WHD)	17 ¹ /8" x 8 ¹ /16" x 13 ¹³ /16"
APPROX. WEIGHT	Net: 71 lb. Shipping: approx. 85 lb.
AC LINE VOLTAGE	UL Rating: 120 Volts, single phase, 60 Hz, AC only
AC POWER REQUIRED	UL Rating: 1.6 kW, 13.2 Amps
SAFETY COMPLIANCE	FCC, DHHS, UL listed
UPC CODE	074000 611023
OPTIONAL ACCESSORIES	RK-220 Charcoal filter for non-ducted installations included with product. Replacement filters available at extra cost.



Design and specifications subject to change without notice.


Dimension Express:

To receive the most current specifications, call Dimension Express at (702) 833-3600 from a fax machine. Enter code 9026 for instructions and a directory of Sharp microwave oven products.

LIMITED WARRANTY: 7 years on magnetron tube, 2 years on all other parts, 2 years on related labor and in-home service. See Operation Manual or your dealer for complete details.

> Sharp Electronics Corporation Sharp Plaza • Mahwah • NJ 07430-2135 1-800-BE-SHARP • www.sharpusa.com

> > © 2002 Sharp Electronics Corporation



Each Sharp Over the Range microwave oven can be easily adapted for either outside ventilation (vertical or horizontal) or non-vented, ductless recirculation. Make sure the top of oven will be at least 66" from the floor and at least 30" from the cooking surface. A separate 15 amp. or greater electrical receptacle must be located in the cabinet directly above the microwave oven.