







Additional Information:

B-165 Series Channel-Framed Mirrors

B-165 Series Standard Stock Sizes

Model No.	Width	Height	
B-165 1624	16"	24"	(41 x 61cm)
 B-165 1824	18"	24"	(46 x 61cm)
 B-165 1830	18"	30"	(46 x 76cm)
 B-165 1836	18"	36"	(46 x 91cm)
 B-165 2430	24"	30"	(61 x 76cm)
 B-165 2436	24"	36"	(61 x 91cm)
B-165 2448	24"	48"	(61 x 122cm)
 B-165 2460	24"	60"	(61 x 152cm)
B-165 3636	36"	36"	(91 x 91cm)
B-165 4836	48"	36"	(122 x 91cm)
B-165 6036	60"	36"	(152 x 91cm)

Special-Order Custom Size Mirrors

- Maximum size mirror: 72" x 60" (183 x 152cm).
- Custom size mirrors lock wall hanger with two concealed theft-resistant screws in bottom of frame.
- To specify special sizes, use Series Number followed by with and height in inches.

B-165 Series Special Order Reflective Surfaces. Resist breakage and provide a necessary safety from broken glass, but differ in color and reflective quality from galvanized glass mirrors.

B-1656 Polished Stainless Steel (up to 72" x 24"; 183 x 61cm)

B-1658 Tempered Glass (up to 72" x 48"; 183 x 122cm)

B-1659 Laminated Glass (up to 72" x 48"; 183 x 122cm)

Notes

- To specify mirrors, use Series Number followed by width and height in inches.
- Width dimension must always be stated first following Series Number.
- Mirrors must be installed with width and height dimensions as ordered.
- Mirror back and wall hanger cannot be installed side ways to reverse width and height dimensions.

Concealed Wall Hanger for Theft-Resistant Mounting

- Simplifies installation.
- Mirror is held flush to wall by integral brackets at top and bottom of mirror back.
- Locking device secures mirror to concealed wall hanger.
- Locking device may be unlocked and mirror removed from wall for reglazing
- Provide minimum 3/4" (19mm) clearance at top of mirror for mounting on wall hanger and 1" (25mm) clearance on each side.

