



Freestanding Range

FPGF3685L S

36" Gas



Product Dimensions

Height (Max.)	47-3/4"
Width	36"
Depth (Including Handle)	28-1/2"

More Easy-To-Use Features

Auto Oven Shut-Off

As an extra safety measure, the oven will automatically shut off after 12 hours.

Low Simmer Burner

Perfect for delicate foods and sauces.

Rapid Clean

For a quick, light oven cleaning.

One-Touch Self Clean


Start the self-cleaning cycle with just the touch of a button.

Fits-More™ Cooktop

The Fits-More™ cooktop features five burners so you can cook more at once.

Sabbath Mode (Star-K® Certified)

Available in:



Signature Features



Pro-Select® Controls

Precise control at your fingertips.



Heavy-Duty Grates and Professional-Style Knobs



Continuous Grates

Continuous Grates make it easy to move heavy pots and pans between burners without lifting.




Even Baking Technology

Our latest technology ensures even baking every time.

Burners	BTU
Right Front	12,000
Right Rear	5,000
Left Front	14,500
Left Rear	9,500
Center Extra Zone	16,000

Features	
Oven Control/Timing System	Pro-Select® Controls
Surface Type	Black Ceramic Glass
Sealed Gas Burners	Yes
Grates	Continuous Cast Iron w/Black Matte Finish
Window	Large
Exterior Door Finish	Real Stainless Steel
Handle Design	Stainless Steel
Exterior Finish (Side Panels)	Black
Convection System	
Oven Cleaning System	Self Clean
Drawer Functionality	Storage
Oven Controls	
Bake/Broil	Yes/ Low and High
Effortless™ Convection Conversion	
Convection Bake/Broil/Roast	
Quick Bake Convection	
PowerPlus® Preheat	
My Favorite	
Chicken Nugget Button	
Pizza Button	
Keep Warm	
Add-a-Minute	
Delay Bake	
Self Clean	2, 3 Hours
Rapid Clean Option	Yes
Delay Clean	Yes
Kitchen Timer/Timed Cook Option	Yes
Auto Oven Shutoff	12 Hours
Lower Drawer Control	
Cooktop Features	
Right Front Burner (BTU)	12,000
Right Rear Burner (BTU)	5,000
Left Front Burner (BTU)	14,500
Left Rear Burner (BTU)	9,500
Center Extra Zone Burner (BTU)	16,000
Oven Features	
Capacity (Cu.Ft.)	3.7
Oven Light	1
Rack Configuration	2 Heavy Duty
Baking System	Even Baking Technology
Broiling System	Vari-Broil™ Hi/Lo
Bake Burner/Broil Burner (BTU)	16,000/12,500
Drawer Racks	
Certifications	
Sabbath Mode (Star-K® Cert.)	Yes
Specifications	
Oven Interior (H x W x D)	15" x 23" x 18-1/2"
Power Supply Connection Location	Middle Bottom Rear
Gas Supply Connection Location	Right Bottom Rear
LP Gas Conversion Kit	Included
Voltage Rating	120V/60Hz/15A
Conn. Load (kW Rating) @ 120 Volts¹	4.2
Amps @ 120 Volts	5
Shipping Weight (Approx.)	220 Lbs.

¹For use on adequately wired 120V, dedicated circuit having 2-wire service with a separate ground wire. Appliance must be grounded for safe operation.



NOTE: For planning purposes only. Always consult local and national electric and gas codes. Refer to Product Installation Guide for detailed installation instructions on the web at frigidaire.com.



Product Dimensions	
A - Height (Max.)	47-3/4"
B - Width	36"
C - Depth (Including Handle)	28-1/2"
Depth with Door Open 90°	44-1/2"

Cutout Dimensions	
Height (Standard)	36"
Width (Min.)	36-1/4"
Depth (Min.)	24"

Accessories information available on the web at frigidaire.com

FRIGIDAIRE


USA • 10200 David Taylor Drive • Charlotte, NC 28262 • 1-800-FRIGIDAIRE • frigidaire.com
CANADA • 5855 Terry Fox Way • Mississauga, ON L5V 3E4 • 1-800-265-8352 • frigidaire.ca

FPGF3685L 12/10

© 2010 Electrolux Home Products, Inc.


Specifications subject to change.
Printed in the U.S.A.

Use these dimensions and clearance instructions for planning purposes only. For detailed installation instructions, refer to installation guide, packed with product, or on the web at frigidaire.com.




When installing appliances adjacent to each other, 20" minimum distance between each appliance required.

When installing built-in cooking appliances in combination, 2" minimum visible gap between appliance faceplates required.



When installing side-by-side refrigerator adjacent to wall, cabinet or another appliance that extends beyond front edge of unit, 20" minimum clearance recommended to allow for optimum 120° to 180° door swing, providing complete drawer/crisper access and removal.


When installing appliance with sliding drawer, swinging or drop-down door directly across from obstructions, provide sufficient clearance for drawer extension or door swings.



When installing appliance with sliding drawer or drop-down door directly across from obstructions, provide sufficient clearance for drawer extension or door swing.


When installing appliance with sliding drawer or drop-down door adjacent to wall, cabinet, or other obstruction that extends beyond front edge of appliance, allow 2" minimum clearance between drawer or door and obstruction.

Use these dimensions and clearance instructions for planning purposes only. For detailed installation instructions, refer to installation guide, packed with product, or on the web at frigidaire.com.




When installing appliances adjacent to each other, 20" minimum distance between each appliance required.

When installing built-in cooking appliances in combination, 2" minimum visible gap between appliance faceplates required.



When installing appliance with sliding drawer, swinging or drop-down door directly across from obstructions, provide sufficient clearance for drawer extension or door swings.

*When installing refrigerator adjacent to wall, cabinet or other appliance that extends beyond front edge of unit, 20" minimum clearance recommended to allow for optimum 140° door swing, providing complete crisper access and removal. (Absolute 3" minimum clearance will ONLY allow for 90° door swing which will provide limited crisper access with restricted removal.)



When installing appliance with sliding drawer or drop-down door directly across from obstructions, provide sufficient clearance for drawer extension or door swing.

When installing appliance with sliding drawer or drop-down door adjacent to wall, cabinet, or other obstruction that extends beyond front edge of appliance, allow 2" minimum clearance between drawer or door and obstruction.

