

AUTO FLOOR GUARD

"We catch it all"



Installation

Take product out of Poly bag and layout on surface that is being covered. Make sure same area is clear of debris or items that could cause indentations or possible tears in fabric. Unfold product completely and either put in sun (if conditions allow) to relax fabric that has been rolled up or allow fabric relax at least 24 hours prior to driving on. If that is not possible be aware fabric will have more wrinkles.

Warranty

AutoFloorGuard warrants your AutoFloorGuard (AFG) to be free from defects in material and workmanship for a period of one (1) year from the date of purchase, subject to the following conditions and limitations:

Conditions:

1. Warranty period is determined by date of purchase from authorized resellers of AutoFloorGuard. (please keep original purchase receipt).

Limitations:

This warranty does not cover the following:

- Improper installation of AFG. (do not follow instructions)
- AFG is not responsible for damage from acts of Nature.
- Placement of the AFG on any surface that is not smooth and flat.
- Use with snow chains or studded snow tires.
- Burns caused by and hot object or open flames. (see Warning below)
- Punctures caused by rocks and other sharp objects. (like shovels and rakes)
- Use of Solvents, Chemicals and Abrasive Detergents to clean the AFG. (example is Bleach)
- Normal wear and tear.
- Discoloration of the vinyl sheeting that may occur over time from direct or indirect light.
- Tire impressions made on the vinyl sheeting, which is considered normal.

Should a defect occur, contact AutoFloorGuard to request a Return Authorization Number. No returns will be accepted without a Return Authorization Number. It is the responsibility of the customer to pay for all shipping costs including insurance. Upon receipt of the returned part(s), AutoFloorGuard will either repair or replace the defective part(s) as it deems necessary.

Caution: The AFG mat is SLIPPERY WHEN WET! Use caution when walking or driving on AFG mat. Removal of fluids and debris is recommended daily. Also Be careful on turning wheels while on mat as this could cause damage.

Warning: Great risk of fire if material is exposed to fire. Do not smoke or use open flame devices (including grills, fire pits, deep fryers, smokers or lanterns) on or around the AFG mat. Do not store flammable liquids (gasoline, kerosene, propane etc) on or around the AFG mat.

Cleaning and Care: A cleaner surface helps maintain longer life for AFG. Clean mat daily with a soft bristle broom, mop, wet or dry vacuum, squeegee. You can use a kitchen liquid soap to help remove dirt. For best results move AFG to end of garage threshold and hose or squeegee out liquid. Be careful if you have oil or other chemical make sure you use proper disposal of these items. (check with your local government for these disposal regulations)

Questions: Please contact your AutoFloorGuard Reseller

