

## Installation Instructions

1. Open package and lay the product out. Orient the product so that the straps and hooks will be on top of the air conditioner and the elastic seams will be on the inside when installed. (figure 1)

*\*Warning-Prior to installing window ac unit with safety net installed check window to ensure that the window sash and frame is installed safely and free of any rot or damage that will prevent it from supporting the AC unit.*

2. Place AC unit face down on a sturdy surface. *\*Warning- Make sure the AC unit is placed on a sturdy surface prior to placing the AC Net over it.*

Slip the AC Net over the back and exterior portion of the unit. Align the seams up with the edges and corners of the AC. (figure 2) *Make sure the 4 elastic seams are on the inside of the net when slipping it on. Make sure the straps with hooks are on the "top" of the air conditioner when it will be in the window and facing towards the front.* (figure3)

*\*Warning- Be sure the net is placed on correctly. The seams align on each side and the net covers the entire portion of the ac that will stick outside the window.*

3. Add slack to the straps by pushing the spring release on the cam buckle and pull the strap through it to elongate them. (figure 4) Be sure there is enough slack in the strapping so that your window will be free to open wide enough. *\*Warning-The straps should be longer than the length of your lower window sash.*

4. Bring the AC Unit to the window opening with net properly aligned and the exterior portion facing out. Prior to placing the AC unit into the window open it only enough to allow you to place the hooks over the top of the sash.

5. Put both of the hooks (figure 5) over the top of the open sash. (figure 6) separate them roughly the width of the AC unit.

*\*Warning-Be sure AC unit is secure and still inside the window opening at this point.*

*\*Warning-DO NOT PUT THE AC UNIT INTO THE WINDOW OPENING UNTIL THE HOOKS ARE SECURED OVER TOP OF THE OPEN WINDOW.*

*(When the net is placed correctly over the air conditioner and the sash hooks are slipped over the top of the window sash the product will help prevent the air conditioner from falling out of the opening)*



(figure 1)



(figure 2)



(figure 3)



(figure 4)



(figure 5)



(figure 6)

6. Open the window enough to place the AC unit where it will go. Adjust the straps so there is not excessive slack by pulling strap through the cam-buckle. Place the AC in the window as specified by the AC manufacturer. Close the window down onto the AC so that it is correctly secured in the window opening as per AC manufacturer's instructions. (figure 7)

7. Pull the strap taut. Place Velcro on the end of the strap and attach to the top of the bracket over the window if desired. (figure 8)

*\*Warning-Be sure to place AC unit in window opening according to manufacturer specifications. Make sure that straps are pulled tight and brackets are over window sash correctly.*

8. To remove follow all directions in reverse order.

*\*Warning-Make sure the AC unit is on the inside of the window and secure before removing the hooks over the window sash.*

## Product Warranty

Limited warranty is in lieu of all other warranties, express or implied, including the warranties of merchantability and fitness for a particular purpose.

This product is warranted against defects in material and workmanship for 1 year from the date of purchase and will be replaced. Proof of purchase is required to validate this warranty.

Improper installation, misuse, modifications, changes or adaptations to this product void the warranty. Liability for failure due to normal wear or usage or consequential and incidental damage is expressly disclaimed.

This product does not cover use in Commercial settings.

Kingdom Products Group shall not be liable for consequential or incidental damages such as property damages, window air conditioner unit damage, incidental expenses or personal injuries sustained from improper use, installation or removal.

In order to file a warranty claim visit our website at, [www.ACSafetyNet.com](http://www.ACSafetyNet.com) or call toll free at 855-227-2338 (855-AC Safety Net)



(figure 7)



(figure 8)

## Additional Warnings and Cautions

*\*The AC Safety Net is for homeowner use for window air conditioners up to 12K btu's units in size only.*  
*\*The AC Safety Net is for use only in properly installed double hung windows free of defects.*  
*\*Carefully read the entire instruction sheet before using product.*

*\*Follow each step as shown.*  
*\*The AC Safety Net is not responsible for failure of the window air conditioner itself.*  
*\*The AC Safety Net is designed to fit windows with a lower sash of up to 42".*  
*\*If ac unit falls out window do not retrieve ac unit by grabbing the rear of the ac unit since the AC unit can slip out of the mesh net if the opening is facing down.*

Easy Installation Video:  
[ACSafetyNet.com/installation](http://www.ACSafetyNet.com/installation)

