
Envision LED Head



DESCRIPTION

Die cast aluminum LED head, pivots vertically 90°, rotates horizontally 360°. Features horizontal locking mechanisms. LED module and optics are modular for ease of replacement. Front air intake design allows airflow past internal heat sink fins to rear exit vents while conserving a clean, thoughtful and seamless form. 18 watt isolated power supply sits within head to avoid further visual impact on track; dimmable digital logic controller operated in constant current mode. Field-replaceable proprietary 18 watt LED module. Three interchangeable optics: 15°, 25° and 40°. Holds up to two PAR16/MR16 lenses or louvers, sold separately.

OTHER



ACCESSORIES & OPTICAL CONTROLS

Colored Lens, Dichroic Lens, Diffuser Lens, Linear Spread Lens, Soft Focus Lens, UV Filter

WEIGHT

 $3.79lb / 1.72kg \pm$

ORDERING INFORMATION

700 SYSTEM ENVL	COLOR TEMP	BEAM SPREAD	LENGTH (A)	FINISH
PJ POWERJACK TT SINGLE-CIRCUIT T~TRAK TT2 TWO-CIRCUIT T~TRAK	L2 LED 2700K L3 LED 3000K	1 15° 2 25° 4 40°	06 6" 12 12" 18 18"	S SATIN NICKEL W WHITE

To order this head for use with Halo*, Juno*, or Lightolier* 120 volt single-circuit track, order as follows:

Substitute 700TT with one of the following: 700TH (fits Halo*), 700TJ (fits Juno*) or 700TI (fits Lightolier*) and by substituting the finish with one of the following: BS (Black/Satin Nickel), BW (Black/White), WS (White/Satin Nickel) or WW (White/White).


*Tech Lighting is not affiliated, nor is it endorsed by any of the companies listed nor does Tech Lighting distribute any of their products.



Skokie, Illinois 60077

T 847.410.4400 F 847.410.4500

Tech Lighting, L.L.C.





©2014 Tech Lighting, L.L.C. All Rights Reserved. The "Tech Lighting" graphic is a registered trademark of Tech Lighting, L.L.C. Tech Lighting reserves the right to change specifications for product improvements without notification.