

LOW-VOLTAGE PENDANTS

Cone Pendant



DESCRIPTION

Case glass cone with reflective white interior or transparent glass cone. Case glass includes low-voltage, 50 watt halogen bi-pin lamp or 8 watt replaceable 500 lumen 80 CRI 3000K LED SORAAA® module. Transparent glass includes low-voltage, 50 watt MR16 flood lamp. Each include six feet of field-cutable suspension cable.

INSTALLATION

Socket terminates with FreeJack male connector, which may be installed into a system connector. Elements ordered with a system prefix include a connector for that system. For use on T~TRAK, order FreeJack version and T~TRAK FreeJack Connector (sold separately).

ACCESSORIES & OPTICAL CONTROLS


Swag Hook

WEIGHT

1.35lb / 0.61kg ±



cobalt



amber



clear



cobalt



red



white

ORDERING INFORMATION

700	SYSTEM	CON	COLOR	FINISH	LAMP
FJ	FREEJACK		A AMBER	Z ANTIQUE BRONZE	12 VOLT HALOGEN
K	KABLE LITE		C CLEAR	C CHROME	-LEDS830 12 VOLT LED 80 CRI 3000K
MP	MONOPOINT		P COBALT	S SATIN NICKEL	-24 24 VOLT HALOGEN
MO	MONORAIL		R RED		
MO2	TWO-CIRCUIT MONORAIL		W WHITE		

Note: Note: MP includes 4" Round Flush Canopy and is available in 120v only (for 277v order as FJ).

Antique Bronze is not available for Kable Lite.

When installing LED option on MO2 only magnetic transformers may be used.



TECH LIGHTING®
 7400 Linder Avenue T 847.410.4400
 Skokie, Illinois 60077 F 847.410.4500

Tech Lighting, L.L.C.

700 ____ CON ____

FIXTURE TYPE: _____

JOB NAME: _____

NOTES: _____
