

John Head



DESCRIPTION

Adjustable head tilts and rotates infinitely. Integral louver lens holder can hold a single glass lens (sold separately) or an eggcrate louver (included). Low-voltage, MR16 lamp of up to 50 watts (not included).

SYSTEM

Available for FreeJack, MonoRail, Two-Circuit MonoRail, and Wall MonoRail. For use on T~trak, order FreeJack version and T~trak FreeJack Connector (sold separately).

INSTALLATION

Socket terminates with FreeJack male connector, which may be installed into a system connector. Elements ordered with a system prefix include a connector for that system. For use on T~TRAK, order FreeJack version and T~TRAK FreeJack Connector (sold separately).

ACCESSORIES & OPTICAL CONTROLS


Colored Lens, Dichroic Lens, Diffuser Lens, Eggcrate Louver, Linear Spread Lens, Soft Focus Lens, UV Filter

WEIGHT

0.2lb / 0.09kg

ORDERING INFORMATION

700	SYSTEM	JON	LENGTH	FINISH
FJ	FREEJACK (MONO POINT)		03 3"	Z ANTIQUE BRONZE
MO	MONORAIL		06 6"	C CHROME
MO2	TWO-CIRCUIT MONORAIL		12 12"	S SATIN NICKEL
WMO	WALL MONORAIL		18 18"	
			24 24"	



TECH LIGHTING®

7400 Linder Avenue T 847.410.4400
 Skokie, Illinois 60077 F 847.410.4500

www.techlighting.com

700 ____ JON ____ ____

FIXTURE TYPE: _____

JOB NAME: _____

NOTES: _____

