

MonoRail Mini-Surface Transformer-300w EL



DESCRIPTION

Truly minimalist design and the industry's smallest 300 watt surface transformer. Constructed of die-cast aluminum and can power lamps totaling up to 300 watts. The transformer is concealed inside a decorative housing with a single integral power feed and fast acting secondary short circuit and overload protection that will safely turn the system off should a short occur. Once the short has been removed, the unit can be reset by simply flipping the wall switch off and on.

INSTALLATION

This product can mount to either a 4" square electrical box with round plaster ring or an octagon electrical box (not included). Rail is installed through the power feed on the canopy to bring power to the run.

DIMMING

Dimmable with a 600 watt low-voltage electronic dimmer. The dimmer is placed on the line side of the transformer. (Consult dimmer manufacturer for specifics).

OTHER INFORMATION

The shortest rigid standoff that can be used with this surface transformer is the 2" rigid standoff (sold separately). If dropping the rail more than 2" below the ceiling, order the desired rigid standoff length and one compatible power extender (sold separately). 12 volt transformers require the use of 12 volt lamps.

ORDERING INFORMATION

700MOMRT30E FINISH	VOLTAGE
Z ANTIQUE BRONZE	120V IN/12V OUT
S SATIN NICKEL	



www.techlighting.com

700MOMRT30E _____

FIXTURE TYPE: _____

JOB NAME: _____

NOTES: _____
