


Rectangular Power Feed Canopy

DUAL-FEED



Shown approx. 35% actual size.



DESCRIPTION

A dual-feed canopy is mounted to the ceiling above the MonoRail run. It brings power to the MonoRail run from a remote transformer (sold separately). The low-voltage leads from the remote transformer are connected to the canopy leads inside the junction box. Isolating connectors are included to isolate power feeds from each other.

INSTALLATION

Mounts to a standard single gang or gem box (not included).

FINISH

Antique bronze, chrome, satin nickel, black, white.
Black and white finish have satin nickel feeds.

USAGE

For use with a dual-feed remote transformer (sold separately).

COMPATIBLE RIGID STANDOFFS

The shortest rigid standoff that can be used with a MonoRail dual-feed canopy is the 2" rigid standoff (sold separately). If dropping the rail more than 2" below the ceiling, order the desired rigid standoff length and two compatible power extenders (sold separately).

WEIGHT

0.65 lb./0.29 kg. ±

ORDERING INFORMATION

700MOPRC402

FINISH

- Z ANTIQUE BRONZE
- C CHROME
- S SATIN NICKEL
- B BLACK
- W WHITE

700MOPRC402 _____

FIXTURE TYPE: _____

JOB NAME: _____



TECH LIGHTING®

7400 Linder Avenue T 847.410.4400
Skokie, Illinois 60077 F 847.410.4500

www.techlighting.com

