
Surface Transformer

SINGLE-FEED, 24 VOLTS 600 WATTS



Shown approx. 20% actual size.



DESCRIPTION

This single-feed surface transformer converts standard 120 line voltage to 24 volts to provide the necessary voltage for powering a MonoRail low-voltage lighting system. It can power lamps totaling up to 600 watts. The transformer is concealed inside a decorative housing with a fast acting secondary circuit breaker that will safely turn the system off should a short occur. Once the short has been removed the breaker can be reset.

INSTALLATION

This product can mount to either 4" square electrical box with round plaster ring or an octagon electrical box (not included). Rail is installed through the power feeds on the canopy to bring power to the run.

DIMMING

Dimmable with a 1000 watt low-voltage magnetic dimmer. The dimmer is placed on the line side of the transformer. (Consult dimmer manufacturer for specifics). This surface transformer includes a preinstalled debuzzing dimming coil to reduce audible noise when using a low-voltage dimmer.

FINISH

Antique bronze, chrome, satin nickel, black, white. Black and white finish have satin nickel feeds.

COMPATIBLE RIGID STANDOFFS

The shortest rigid standoff that can be used with this surface transformer is the 5" rigid standoff (sold separately). If dropping the rail more than 5" below the ceiling, order the desired rigid standoff length and one compatible power extender (sold separately).

OPTIONS

This surface transformer may be plugged in with the addition of a Plug Option, a 16 foot cord with inline switch two feet from the plug (sold separately).

REQUIRED USAGE

24 volt transformers require the use of 24 volt lamps.

WEIGHT

20.40 lb./9.25 kg. ±

ORDERING INFORMATION

700MOSRT624D FINISH Z ANTIQUE BRONZE C CHROME S SATIN NICKEL B BLACK W WHITE



7400 Linder Avenue Skokie, Illinois 60077 T 847.410.4400 F 847.410.4500

www.techlighting.com

