

**Envision Head**



**DESCRIPTION**

Specification grade head with precision internal gearing mechanisms that allow for hot aiming and are self-locking. Rotates 360° and pivots 0° to 90°. Up to two lenses or louvers (sold separately) are held captive inside the lamp cartridge which includes an integral glare reducing snoot. Lamp cartridge and lens orientation adjust 180°. Lamp cartridge is keyed to maintain accurate focus during relamping. All functionality can be fine-tuned using a phillips or flat head screwdriver and with the guide of accompanying markings. Low-voltage, MR16 lamp of up to 50 watts (not included).

**SYSTEM**

Available for FreeJack, MonoRail, and Two-Circuit MonoRail. For use on T~trak, order FreeJack version and T~trak FreeJack Connector (sold separately).

**INSTALLATION**

Socket terminates with FreeJack male connector, which may be installed into a system connector. Elements ordered with a system prefix include a connector for that system. For use on T~TRAK, order FreeJack version and T~TRAK FreeJack Connector (sold separately).

**ACCESSORIES & OPTICAL CONTROLS**


Colored Lens, Dichroic Lens, Diffuser Lens, Eggcrate Louver, Linear Spread Lens, Soft Focus Lens, UV Filter

**WEIGHT**

1.19lb / 0.54kg

**ORDERING INFORMATION**

700	SYSTEM	ENV	LENGTH	FINISH	LAMP
FJ	FREEJACK (MONO POINT)		03 3.5"	S SATIN	12 VOLT
MO	MONORAIL		07 7.5"	NICKEL	HALOGEN
MO2	TWO-CIRCUIT MONORAIL				



**TECH LIGHTING®**

7400 Linder Avenue T 847.410.4400  
 Skokie, Illinois 60077 F 847.410.4500

[www.techlighting.com](http://www.techlighting.com)

700 \_\_\_\_ ENV \_\_\_\_

FIXTURE TYPE: \_\_\_\_\_

JOB NAME: \_\_\_\_\_

NOTES: \_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

