



#### 87823BK

# Coupler for MX Interlink 2 Cords

This state-of-the-art LED light bar raises under cabinet lighting to a whole new level. The crisp white light illuminates without shadows, and its direct wire plug in and easy clip installation make the CounterMax MX-L Series under cabinet lighting convenient as well as beautiful.

F	ini	si
R	lac	:k

# Lamping

# Number of Bulbs Light Type Bulb Type Max Wattage Rated Life Rated Lumens Color Temp Bulb(s) Included No Light Up/Down N/A Beam Spread CRI

### Glass/Shade

# Measurements Width Height

0.4" Length 0.6" Exension 0" **Back Plate Width** 0.0" **Back Plate Height** 0.0" HCO 0" Min Overall Height N/A **Max Overall Height** N/A **Hanging Weight** 0.0 lbs

# Product Category

**Under Cabinet Accessory** 

#### Shipping

2.1"

Jilippilig	
Carton Weight	0.0 lbs
Carton Width	
Carton Height	
Carton Length	
Carton Cubic Feet	0
Master Pack	0
Master Pack Weight	0.0 lbs
Master Pack Width	0.0"
Master Pack Height	0.0"
Master Pack Length	0.0"
Master Cubic Feet	0
UPS Shippable	Yes

## Certification

UL/ETL/CSA	
Energy Star	No
CA Title 24	No
CA Title 20	No
ADA	No

# Other

**UPC Code** 

# **Equivalents**

Incandescent Fluorescent

Maxim Lighting International, ET2 Contemporary Lighting and all designs, logos and images © 2010 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Products are subject to revision in design and/or construction to conform to changes in UL and/or CSA standards, or that which may be required by law or availability of material.

Maxim Lighting International products are UL and CSA approved.

Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.