



Product Specifications - 5849WSOI

Job Name:	Job Type:
Quantity:	Comments:

Image
Not
Available

5849WSOI
2-Light Flush Mount

Finish
Oil Rubbed Bronze

Glass/Shade
Wilshire

Product Category
Flush Mount

Lamping
Number of Bulbs 2
Light Type Incandescent
Bulb Type MB
Max Bulb Wattage 60
Max Fixture Wattage 120
Rated Life ±2,500 Hours
Rated Lumens ±1,344
Color Temp ±2,700 K
Bulb(s) Included No
Light Up/Down N/A
Beam Spread N/A
CRI N/A
Photo Cell Included N/A
Ballast N/A

Measurements
Width 11.5"
Height 6.0"
Length N/A
Extension N/A
Back Plate Width N/A
Back Plate Height N/A
HCO N/A
Min Overall Height N/A
Max Overall Height N/A
Hanging Weight 2.3 lbs
Height Adjustable N/A
Slope N/A

Shipping
Carton Weight 2.3 lbs
Carton Width 6"
Carton Height 11"
Carton Length 11"
Carton Cubic Feet 0.45
Master Pack 1
Master Pack Weight N/A
Master Pack Width N/A
Master Pack Height N/A
Master Pack Length N/A
Master Cubic Feet N/A
UPS Shippable Yes

Certification
UL/ETL/CSA Dry
Energy Star No
CA Title 24 No
CA Title 20 No
ADA No

Other
UPC Code 783209584921
Shades Included N/A
Crystals Included N/A
Diffuser Included N/A
Conversion Kit N/A
Material Iron

Equivalents
Incandescent Watts N/A
Fluorescent Watts N/A

Maxim Lighting International and all designs, logos and images © 2010 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Products are subject to revision in design and/or construction to conform to changes in UL and/or CSA and/or ETL standards, or that which may be required by law or availability of material.

Maxim Lighting International products are UL, ETL or CSA approved.

Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.