

Lighting Your Life Since 1970

Product Specifications - 21464NKPN		
Job	Name:	Job Type:
Qu	antity:	Comments



21464NKPN

Chantilly 6-Light Chandelier

Finish Polished Nickel Glass/Shade

Product Category Single-Tier Chandelier

Lamping

Lamping	
Number of Bulbs	6
Light Type	Xenon
Bulb Type	G9
Max Bulb Wattage	60
Max Fixture Wattage	360
Rated Life	±2,000 Hours
Rated Lumens	±4,800
Color Temp	±2,900 K
Bulb(s) Included	Yes
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	Standard

IVI	eas	sur	em	ent	S

14.0"
22.0"
N/A
11.7 lbs
N/A
N/A
36"
180"
6.0"
3.0"
N/A

Shinning

Snipping	
Carton Weight	11.7 lbs
Carton Width	16'
Carton Height	19'
Carton Length	16'
Carton Cubic Feet	2.77
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes

Certification

Certification	Other	
UL Standard	Dry UPC Code	783209094062
Energy Star	No Shades Included	N/A
CA Title 24	No Crystals Included	N/A
CA Title 20	No Diffuser Included	N/A
ADA	No Conversion Kit	N/A
Dark Sky	N/A Material	N/A

Othor

Equivalents

Incandescent Watts	N/A
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2010 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Products are subject to revision in design and/or construction to conform to changes in UL and/or CSA and/or ETL standards, or that which may be required by law or availability of material. Maxim Lighting International products are UL, ETL or CSA approved. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.