


Product Specifications



87906SA - CounterMax MX-L 30" LED Under Cabinet Light

| | | |
|---|--------------------------------------|----------------------|
|  | Fixture Dimensions | |
| | Width: 2" | Height: 1" |
| | Length: 30" | Extension: |
| | HCO: | Back Plate: x |
| | Chain: 0' | Wire: 0' |
| | Bulbs | |
| | Quantity: 6 | Type: LED |
| | Wattage: 1w Max | Included: No |
| | Certifications/Qualifications | |
| | Energy Star: No | |
| | Other | |
| | UPC: 783209064553 | |
| | Note: | |
| <p>Item: 87906SA</p> <p>Collection: CounterMax MX-L</p> <p>Finish: Satin Aluminum</p> <p>Glass:</p> | | |

This state-of-the-art LED light bar raises under cabinet lighting to a whole new level. The crisp white light illuminates without shadows, and its direct wire plug in and easy clip installation make the CounterMax MX-L Series under cabinet lighting convenient as well as beautiful.

| Shipping Information | | | | | | | | | |
|----------------------|--------|--------|-------|--------|-------------|--------|--------|-------|--------|
| Individual | Weight | Length | Width | Height | Case | Weight | Length | Width | Height |
| Qty: 1 | 11 lbs | 39" | 3" | 2" | Qty: | 0 lbs | | | |

Maxim Lighting International, ET2 Contemporary Lighting and all designs, logos and images © 2008 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Products are subject to revision in design and/or construction to conform to changes in UL and/or CSA standards, or that which may be required by law or availability of material.

Maxim Lighting International products are UL and CSA approved.

Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighting 35 lbs. or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.