



12053WTOI

Nexus 4-Light Entry Foyer Pendant

The **Nexus** collection is the true standard for contemporary lighting. The flat rectangular tube arm forms to a perfect angle and comes finished in choice of **Satin Nickel** or **Oil Rubbed Bronze**. The **White** fabric drum shade is trimmed with metal rings in matching finish for a clean, tailored look.

Finish

Oil Rubbed Bronze

Glass/Shade

Product Category

Entry Foyer Pendant

Lamping

Number of Bulbs	4
Light Type	Incandescent
Bulb Type	MB
Max Wattage	100
Rated Life	2500
Rated Lumens	4,600
Color Temp	2700
Bulb(s) Included	No
Light Up/Down	N/A
Beam Spread	
CRI	

Measurements

Width	22.0"
Height	24.5"
Length	N/A
Extension	N/A
Back Plate Width	0.0"
Back Plate Height	0.0"
HCO	0"
Min Overall Height	N/A
Max Overall Height	N/A
Hanging Weight	0.0 lbs

Shipping

Carton Weight	0.0 lbs
Carton Width	
Carton Height	
Carton Length	
Carton Cubic Feet	0
Master Pack	1
Master Pack Weight	0.0 lbs
Master Pack Width	0.0"
Master Pack Height	0.0"
Master Pack Length	0.0"
Master Cubic Feet	0
UPS Shippable	Oversize

Certification

UL/ETL/CSA	
Energy Star	No
CA Title 24	No
CA Title 20	No
ADA	No

Other

UPC Code

Equivalents

Incandescent
Fluorescent

Maxim Lighting International, ET2 Contemporary Lighting and all designs, logos and images © 2010 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Products are subject to revision in design and/or construction to conform to changes in UL and/or CSA standards, or that which may be required by law or availability of material.

Maxim Lighting International products are UL and CSA approved.

Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.