

## Lighting Your Life Since 1970

	Product Specifications - 10120WSOI		
ı	Job Name:	Job Type:	
l			
ĺ	Quantity:	Comments	
ı			



## 10120WSOI

**Basix 2-Light Semi-Flush Mount** 

N/A

Finish	Glass/Shade	<b>Product Category</b>
Oil Rubbed Bronze	Wilshire	Semi-Flush Mount

**Canopy Length** 

Lamping	7
Number	C

Number of Bulbs	2
Light Type	Incandescent
Bulb Type	MB
Max Bulb Wattage	100
Max Fixture Wattage	200
Rated Life	±2,500 Hours
Rated Lumens	±2,300
Color Temp	±2,700 K
Bulb(s)	Not Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	Standard

Measurements	
Width	14.0"
Height	10.0"
Length	N/A
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
НСО	N/A
Min Overall Height	N/A
Max Overall Height	N/A
Hanging Weight	3.1 lbs
Height Adjustable	N/A
Slope	N/A
Chain Length	N/A
Wire Length	N/A
Canopy Width	N/A
Canopy Height	N/A

	Shipping	
"	Carton Weight	3.1 lbs
"	Carton Width	15"
4	Carton Height	10"
4	Carton Length	15"
4	Carton Cubic Feet	1.30
4	Master Pack	1
4	Master Pack Weight	N/A
4	Master Pack Width	N/A
4	Master Pack Height	N/A
s	Master Pack Length	N/A
4	Master Cubic Feet	N/A
4	UPS Shippable	Yes
	-	

Certification		Other		Equivalents	
Safety Rating	Dry	UPC Code	783209025790	Incandescent Watts	N/A
Energy Star	No	Shades Included	N/A	Fluorescent Watts	N/A
CA Title 24	No	Crystals Included	N/A		
CA Title 20	No	Diffuser Included	N/A		
ADA	No	Conversion Kit	0		
Dark Sky	N/A	Material	Iron		

Maxim Lighting International and all designs, logos and images © 2013 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.