

Lighting Your Life Since 1970

Product Specifications - 92260FTOI			
Jol	b Name:	Job Type:	
Qu	uantity:	Comments	



92260FTOI

Contour 1-Light Mini Pendant

N/A

N/A

N/A

FinishGlass/ShadeProduct CategoryOil Rubbed BronzeFrostedMini Pendant

12	m	n	ın	_
La	,,,	w	,,,	ч

Lamping	
Number of Bulbs	1
Light Type	Incandescent
Bulb Type	MB
Max Bulb Wattage	100
Max Fixture Wattage	100
Rated Life	±2,500 Hours
Rated Lumens	±1,150
Color Temp	±2,700 K
Bulb(s)	Not Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	Standard

Measurements	
Width	7.5"
Height	
Length	N/A
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
HCO	N/A
Min Overall Height	N/A
Max Overall Height	N/A
Hanging Weight	1.2 lbs
Height Adjustable	N/A
Slope	N/A
Chain Length	N/A
Wire Length	72"

Shipping	
Carton Weight	1.2 lbs
Carton Width	10"
Carton Height	8"
Carton Length	13"
Carton Cubic Feet	0.59
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes

Certification	Other	Equivalents

Canopy Width

Canopy Height

Canopy Length

OCI (III CULIOII		Other		Equivalents	
Safety Rating	Dry	UPC Code	783209060067	Incandescent Watts	N/A
Energy Star	No	Shades Included	N/A	Fluorescent Watts	N/A
CA Title 24	No	Crystals Included	N/A		
CA Title 20	No	Diffuser Included	N/A		
ADA	No	Conversion Kit	N/A		
Dark Sky	N/A	Material	Steel		

Maxim Lighting International and all designs, logos and images © 2013 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.