

Lighting Your Life Since 1970

Product Specifications - 1015BK		
Job Name:	Job Type:	
Quantity:	Comments	



1015BK

Madrona Cast 3-Light Outdoor Pole/Post Lantern

Product Category Finish Glass/Shade Black Outdoor Pole/Post Mount

Number of Bulbs	3
Light Type	Incandescent
Bulb Type	CA
Max Bulb Wattage	60
Max Fixture Wattage	180
Rated Life	±1,500 Hours
Rated Lumens	±2,016
Color Temp	±2,700 K
Bulb(s)	Not Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	Standard Dimmer

Seedy	
Measurements Width	

Measurente	
Width	9.5"
Height	18.5"
Length	N/A
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
НСО	N/A
Min Overall Height	N/A
Max Overall Height	N/A
Hanging Weight	3.6 lbs
Height Adjustable	N/A
Slope	N/A
Chain Length	N/A
Wire Length	N/A
Canopy Width	N/A
Canopy Height	N/A
Canopy Length	N/A

Shinning

Shipping	
Carton Weight	3.6 lbs
Carton Width	9'
Carton Height	16'
Carton Length	11'
Carton Cubic Feet	0.87
Master Pack	4
Master Pack Weight	22.5 lbs
Master Pack Width	19.3
Master Pack Height	16.0
Master Pack Length	21.5
Master Cubic Feet	3.83
UPS Shippable	Yes

N/A N/A

Certification Other **Equivalents**

00.1041.0		0 11101		294.74.00
Safety Rating	Wet	UPC Code	783209101524	Incandescent Watts
Energy Star	No	Shades Included	N/A	Fluorescent Watts
CA Title 24	No	Crystals Included	N/A	
CA Title 20	No	Diffuser Included	N/A	
ADA	No	Conversion Kit	N/A	
Dark Sky	N/A	Material	Die Cast Aluminum	

Maxim Lighting International and all designs, logos and images © 2013 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.