

Lighting Your Life Since 1970

Product Specifications - 11242SAOI			
Job Name:	Job Type:		
Quantity:	Comments		



11242SAOI

Symphony 3-Light Invert Bowl Pendant

Finish Oil Rubbed Bronze

Lamping Number of Bulbs

Dimmable

Nullibel of Bulbs	3
Light Type	Incandescent
Bulb Type	MB
Max Bulb Wattage	60
Max Fixture Wattage	180
Rated Life	±2,500 Hours
Rated Lumens	±2,016
Color Temp	±2,700 K
Bulb(s)	Not Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A

Glass/Shade
Screen Amber

Measurements

Canopy Length

Other

wiatn	27.0"
Height	29.5"
Length	N/A
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
HCO	N/A
Min Overall Height	N/A
Max Overall Height	N/A
Hanging Weight	19.9 lbs
Height Adjustable	N/A
Slone	N/A

N/A Slope **Chain Length** 36" Wire Length 180" **Canopy Width** N/A **Canopy Height** N/A

Product Category

Invert Bowl Pendant

Shipping	
Carton Weight	19.9 lbs
Carton Width	25"
Carton Height	24"
Carton Length	25"
Carton Cubic Feet	8.51
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes

ertificat	ion		

Ballast/Driver/Transformer

Certification		Other	
Safety Rating	Dry	UPC Code	783209009745
Energy Star	No	Shades Included	N/A
CA Title 24	No	Crystals Included	N/A
CA Title 20	No	Diffuser Included	Yes
ADA	No	Conversion Kit	N/A
Dark Sky	N/A	Material	Iron

No

Standard

Equivalents

N/A

Incandescent Watts	N/A
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2013 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.