

Lighting Your Life Since 1970

	Product Specifications - 5833FTPB	
ſ	Job Name:	Job Type:
L		
ſ	Quantity:	Comments
I		



5833FTPB

Essentials 2-Light Semi-Flush Mount

Finish

Polished Brass

Lamping

Number of Bulbs	2
Light Type	Incandescent
Bulb Type	MB
Max Bulb Wattage	100
Max Fixture Wattage	200
Rated Life	±2,500 Hours
Rated Lumens	±2,300
Color Temp	±2,700 K
Bulb(s)	Not Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	Standard

G	lass	/Sh	ad	e

Frosted

Manauramanta
Measurements

Width	14.5"
Height	14.0"
Length	N/A
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
HCO	N/A
Min Overall Height	N/A
Max Overall Height	N/A
Hanging Weight	4.7 lbs
Height Adjustable	N/A
Slope	N/A
Chain Length	N/A
Wire Length	N/A
Canopy Width	N/A
Canopy Height	N/A

Product Category

Semi-Flush Mount

S	Shipping	
С	arton Weight	4.7 lbs
C	arton Width	15"
C	arton Height	15"
C	arton Length	16"
C	arton Cubic Feet	1.98
N	laster Pack	1
N	laster Pack Weight	N/A
N	laster Pack Width	N/A
N	laster Pack Height	N/A
N	laster Pack Length	N/A
N	laster Cubic Feet	N/A
U	IPS Shippable	Yes

Certification

Safety Rating

Energy Star

CA Title 24

CA Title 20

Dark Sky

ADA

Other

Dry

No

No

No

No

N/A

Canopy Length

Othici	
UPC Code	783209583320
Shades Included	N/A
Crystals Included	N/A
Diffuser Included	N/A
Conversion Kit	N/A
Material	Iron

Equivalents

N/A

Incandescent Watts	N/A
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2013 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.