

Lighting Your Life Since 1970

Product Specifications - 5883CLWT		
Job	Name:	Job Type:
Quar	ntity:	Comments



5883CLWT

Essentials 2-Light Flush Mount

Finish White

Lamping
Number of Bulbs

Number of Buibs	2
Light Type	Incandescent
Bulb Type	MB
Max Bulb Wattage	60
Max Fixture Wattage	120
Rated Life	±2,500 Hours
Rated Lumens	±1,344
Color Temp	±2,700 K
Bulb(s)	Not Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	Standard

Glass/Shade

Clear

Measurements

wiath	
Height	
Length	
Extension	
Back Plate Width	
Back Plate Height	
HCO	
Min Overall Height	
Max Overall Height	
Hanging Weight	
Height Adjustable	
Slope	
Chain Length	
Wire Length	
Canopy Width	
Canopy Height	

Product Category

Flush Mount

~	hı	n	n	ını	
9	ш	μ	P	ш	
_		• . •	•		

N/A N/A

N/A

N/A

	Shipping	
9.5"	Carton Weight	2.7 lbs
4.5"	Carton Width	12"
N/A	Carton Height	6"
N/A	Carton Length	12"
N/A	Carton Cubic Feet	0.49
N/A	Master Pack	8
N/A	Master Pack Weight	26.0 lbs
N/A	Master Pack Width	24.0"
N/A	Master Pack Height	13.5"
2.7 lbs	Master Pack Length	24.0"
N/A	Master Cubic Feet	4.50
N/A	UPS Shippable	Yes
N/A		

Certification

Safety Rating Dry **Energy Star** No CA Title 24 No CA Title 20 No **ADA** No Dark Sky N/A

Canopy Length

Other	
UPC Code	783209588318
Shades Included	N/A
Crystals Included	N/A
Diffuser Included	N/A
Conversion Kit	N/A
Material	Iron

Equivalents

Incandescent Watts	N/A
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2013 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.