



Lighting Your Life Since 1970

Product Specifications - 87920BK

Job Name:	Job Type:
Quantity:	Comments:



**87920BK**  
Flush Mount EE 1-Light Outdoor Ceiling Mount

**Finish**  
Black

**Glass/Shade**  
Frosted

**Product Category**  
Outdoor Ceiling Mount

**Lamping**

Number of Bulbs	1
Light Type	Fluorescent
Bulb Type	GU24
Max Bulb Wattage	13
Max Fixture Wattage	13
Rated Life	±10,000 Hours
Rated Lumens	±900
Color Temp	±2,700 K
Bulb(s)	Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	81-82
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	No

**Measurements**

Width	11.5"
Height	4.5"
Length	N/A
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
HCO	N/A
Min Overall Height	N/A
Max Overall Height	N/A
Hanging Weight	3.5 lbs
Height Adjustable	N/A
Slope	N/A
Chain Length	N/A
Wire Length	N/A
Canopy Width	N/A
Canopy Height	N/A
Canopy Length	N/A

**Shipping**

Carton Weight	3.5 lbs
Carton Width	6"
Carton Height	11"
Carton Length	11"
Carton Cubic Feet	0.37
Master Pack	6
Master Pack Weight	26.2 lbs
Master Pack Width	17.5"
Master Pack Height	11.6"
Master Pack Length	22.4"
Master Cubic Feet	2.65
UPS Shippable	Yes

**Certification**

Safety Rating	Damp
Energy Star	No
CA Title 24	Yes
CA Title 20	No
ADA	No
Dark Sky	N/A

**Other**

UPC Code	783209019720
Shades Included	N/A
Crystals Included	N/A
Diffuser Included	N/A
Conversion Kit	N/A
Material	Die Cast Aluminum

**Equivalents**

Incandescent Watts	82
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2013 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.