

Lighting Your Life Since 1970

	Product Specifications - 87449WT						
ı	Job Name:	Job Type:					
l							
ĺ	Quantity:	Comments					
ı							



Certification

Safety Rating

Energy Star

CA Title 24

CA Title 20

Dark Sky

ADA

87449WT

CounterMax MX-X12-LX 1-Light Xenon Under Cabinet

Equivalents

Incandescent Watts

Fluorescent Watts

N/A

N/A

783209074798

N/A

N/A

N/A

N/A

Aluminum

Finish White		Glass/Shade		Product Category Under Cabinet	
Lamping		Measurements		Shipping	
Number of Bulbs	1	Width	5.0"	Carton Weight	0.7 lbs
Light Type	Xenon	Height	1.0"	Carton Width	8"
Bulb Type	12V Wedge T5 Xelogen	Length	7.0"	Carton Height	4"
Max Bulb Wattage	18	Extension	N/A	Carton Length	10"
Max Fixture Wattage	18	Back Plate Width	N/A	Carton Cubic Feet	0.16
Rated Life	±10,000 Hours	Back Plate Height	N/A	Master Pack	5
Rated Lumens	±264	HCO	N/A	Master Pack Weight	11.1 lbs
Color Temp	±2,900 K	Min Overall Height	N/A	Master Pack Width	8.5"
Bulb(s)	Included	Max Overall Height	N/A	Master Pack Height	20.5"
Light Up/Down	N/A	Hanging Weight	0.7 lbs	Master Pack Length	11.0"
Beam Spread	N/A	Height Adjustable	N/A	Master Cubic Feet	1.11
CRI	N/A	Slope	N/A	UPS Shippable	Yes
Photo Cell Included	N/A	Chain Length	N/A		
Ballast/Driver/Transformer	Yes	Wire Length	N/A		
Dimmable	Low-Voltage	Canopy Width	N/A		
		Canopy Height	N/A		
		Canopy Length	N/A		

Maxim Lighting International and all designs, logos and images © 2013 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Other

Dry

No

No

No

No

N/A

UPC Code

Material

Shades Included

Crystals Included

Diffuser Included

Conversion Kit

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.