

## Lighting Your Life Since 1970

Glass/Shade

Product Specifications - 19053FTOI				
Job Name:	Job Type:			
Quantity:	Comments			

**Product Category** 



**Finish** 

## 19053FTOI Elle 3-Light Bath Vanity

CII D. L. L. D.		<u> </u>		Troduct Category	
Oil Rubbed Bronze		Frosted		Bath Vanity	
Lamping		Measurements		Shipping	
Number of Bulbs	3	Width	20.5"	Carton Weight	8.4 lbs
Light Type	Xenon	Height	5.3"	Carton Width	10"
Bulb Type	G9 Frost	Length	N/A	Carton Height	8"
Max Bulb Wattage	60	Extension	6"	Carton Length	24"
Max Fixture Wattage	180	Back Plate Width	N/A	Carton Cubic Feet	1.02
Rated Life	±2,000 Hours	Back Plate Height	N/A	Master Pack	1
Rated Lumens	±2,400	HCO	N/A	Master Pack Weight	N/A
Color Temp	±2,900 K	Min Overall Height	N/A	Master Pack Width	N/A
Bulb(s)	Included	Max Overall Height	N/A	Master Pack Height	N/A
Light Up/Down	N/A	Hanging Weight	8.4 lbs	Master Pack Length	N/A
Beam Spread	N/A	Height Adjustable	N/A	Master Cubic Feet	N/A
CRI	N/A	Slope	N/A	UPS Shippable	Yes
Photo Cell Included	N/A	Chain Length	N/A		
Ballast/Driver/Transformer	No	Wire Length	N/A		
Dimmable	Standard	Canopy Width	N/A		
		Canopy Height	N/A		
		Canopy Length	N/A		

Certification		Other		Equivalents	
Safety Rating	Damp	UPC Code	783209088894	Incandescent Watts	N/A
Energy Star	No	Shades Included	N/A	Fluorescent Watts	N/A
CA Title 24	No	Crystals Included	N/A		
CA Title 20	No	Diffuser Included	N/A		
ADA	No	Conversion Kit	N/A		
Dark Sky	N/A	Material	N/A		

Maxim Lighting International and all designs, logos and images © 2013 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.