

Lighting Your Life Since 1970

Product Specifications - 22173SWPC		
Job Name:	Job Type:	
Quantity:	Comments	



22173SWPC

Elan 3-Light Pendant

Finish Glass/Shade **Product Category** Polished Chrome Satin White Invert Bowl Pendant

Lamping
Number of
Light Type
Double Trees

Lamping	
Number of Bulbs	3
Light Type	Incandescent
Bulb Type	MB
Max Bulb Wattage	100
Max Fixture Wattage	300
Rated Life	±2,500 Hours
Rated Lumens	±3,450
Color Temp	±2,700 K
Bulb(s)	Not Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	Standard

Measurements	
Width	20.0"
Height	24.0"
Length	N/A
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
HCO	N/A
Min Overall Height	N/A
Max Overall Height	69.5"
Hanging Weight	N/A
Height Adjustable	Yes
Slope	N/A
Chain Length	N/A
Wire Length	180"
Canopy Width	N/A
Canopy Height	N/A
Canopy Length	N/A

	Shipping	
"	Carton Weight	N/A
"	Carton Width	24"
4	Carton Height	9"
4	Carton Length	24"
4	Carton Cubic Feet	2.98
4	Master Pack	1
4	Master Pack Weight	N/A
Α."	Master Pack Width	N/A
"	Master Pack Height	N/A
4	Master Pack Length	N/A
s	Master Cubic Feet	N/A
4	UPS Shippable	Yes
^		

Cofety Detine	Day LIDC Code	702
Certification	Other	

Safety Rating	Dry	UPC Code	783209088115
Energy Star	No	Shades Included	N/A
CA Title 24	No	Crystals Included	N/A
CA Title 20	No	Diffuser Included	N/A
ADA	No	Conversion Kit	N/A
Dark Sky	N/A	Material	N/A

Equivalents	
Incandescent Watts	N/A
Fluorescent Watts	N/A

Maxim Lighting International and all designs, logos and images © 2013 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.