

## Lighting Your Life Since 1970

Product Specifications - 22294BKSN		
Job	Name:	Job Type:
Qua	antity:	Comments



## 22294BKSN

**Rapture 5-Light Pendant** 

**Finish** Satin Nickel Glass/Shade

**Product Category** 

Single Pendant

Lamping	
Number of Bulbs	5
Light Type	Xenon
Bulb Type	G9
Max Bulb Wattage	50
Max Fixture Wattage	250
Rated Life	±2,000 Hours
Rated Lumens	±3,750
Color Temp	±2,900 K
Bulb(s)	Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	Standard

Measurements	
Width	16.0"
Height	15.3"
Length	N/A
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
HCO	N/A
Min Overall Height	N/A
Max Overall Height	58.3"
Hanging Weight	9.3 lbs
Height Adjustable	Yes
Slope	N/A
Chain Length	N/A
Wire Length	180"
Canopy Width	N/A
Canopy Height	N/A
Canopy Length	N/A

Shipping	
Carton Weight	9.3 lbs
Carton Width	19"
Carton Height	12"
Carton Length	19"
Carton Cubic Feet	2.34
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes

_	-4:5:	4:
	rtifica	
-	ı cirica	

Ot	ther	
Dry <b>UF</b>	PC Code	783209088993
No Sh	nades Included	N/A
No Cr	rystals Included	N/A
No <b>Di</b>	ffuser Included	N/A
No Co	onversion Kit	N/A
N/A <b>M</b> a	aterial	N/A
	Dry UI No SI No Ci No Di	No Shades Included No Crystals Included No Diffuser Included No Conversion Kit

Equivalents	
Incandescent Watts	

Fluorescent watts	`

N/A

Maxim Lighting International and all designs, logos and images © 2013 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.