



Description:

The Bling I Down MP2 pendant includes a 2" kiss mono-point canopy with integral 2" J-box and 75 Watt transformer. Standard cable length of 59" can be field-cut or specified when ordering. May be specified with 4" kiss mono-point canopy by adding /MP to the part number.

Part Numbers:

220173bz/MP2	bronze, amber glass
220173ch/MP2	chrome, amber glass
220173mc/MP2	matte chrome, amber glass
220178bz/MP2	bronze, white glass
220178ch/MP2	chrome, white glass
220178mc/MP2	matte chrome, white glass
221840bz/MP2	bronze, black glass
221840ch/MP2	chrome, black glass
221840mc/MP2	matte chrome, black glass
221841bz/MP2	bronze, gold glass
221841ch/MP2	chrome, gold glass
221841mc/MP2	matte chrome, gold glass
221842bz/MP2	bronze, silver glass
221842ch/MP2	chrome, silver glass
221842mc/MP2	matte chrome, silver glass

Technical Specs:

120V AC, 50/60Hz input
 11.7 AC output
 50VA, 49W for 1 (maximum 50 Watt lamp)
 GY6.35 socket
 Suitable for dry locations only
 2 1/4" hole cutout
 Required material thickness 3/16" - 1 1/16"
 Not thru-wire rated
 Short circuit protection
 Overload protection
 Thermal protection
 Dimmable
 May also be specified with MR16 socket